

MAHINDRA IMPLEMENT ADVANTAGE

Mahindra offers a huge selection of performance-matched implements to help you accomplish any task you wish to tackle: Mowers, Post Hole Diggers, Landscape Rakes, Box Blades, Rotary Broom, Rear Blade, Snow Blower, Tiller, and Trailer Mover.



eMAX SERIES ATTACHMENTS

TRACTOR	eMAX 20S HST	eMAX 20S HST CAB	eMAX 22L G	eMAX 22L HST	eMAX 25L HST	eMAX 25L HST CAB
LOADER MODEL	23L		25LSK			
Standard Bucket Size [in]	48		50			
Maximum Lift Height [in]	71.3		75.3			
Dig Depth [in]	5.3		4.1			
Lift Capacity to Full Height at Pivot Pin [lbs]	617		900			
Breakout Force [lbs]	1235		2000			
Shipping Weight [lbs]	419		549			
BACKHOE MODEL	23B	N/A	26B	N/A		
Standard Bucket Size [in]	12	N/A	12	N/A		
Maximum Dig Depth [in]	71.5	N/A	80	N/A		
Dig Depth 2' Flat Bottom [in]	63	N/A	78.5	N/A		
Dig Force Bucket [lbs]	2050	N/A	2270	N/A		
Dig Force Dipper [lbs]	1256	N/A	1248	N/A		
Shipping Weight [lbs]	606	N/A	610	N/A		
MOWER MODEL	50M		62M			
Type	Side Discharge		Side Discharge			
Cutting Width [in]	54		60			
Cutting Height [in]	1-4		1-4			
Transport Height [in]	5.12		5			
Lift Linkage Type	Lower Link Lift		Wrap Around Type			
Height Adjustment	Dial Gauge		Dial Gauge			
Number of Blades	3		3			
Blade Tip Speed [FPM]	18000		17350			
Weight [lbs]	272		411			
Adjustable Anti-Scalp Wheels	4		4			

eMAX SERIES SPECIFICATIONS

TRACTOR	eMAX 20S HST	eMAX 20S HST CAB	eMAX 22L G	eMAX 22L HST	eMAX 25L HST	eMAX 25L HST CAB
ENGINE						
Type	Four-stroke, Naturally Aspirated, Indirect Injection, Water-cooled Diesel Engine, Complies with US TIER-4 Final Norms					
Engine HP (kW) @ RPM	19.4 (14.5) @ 3000		22 (16) @ 2600		24 (18) @ 2600	
Displacement [in ³ (cc)]	60.6 (993)		71.7 (1175)			
Number of Cylinders	3					
Bore & Stroke [in]	2.91 x 3.03		3.07 x 3.23			
Fuel Tank [gal (L)]	6.6 (25)		5.8 (22)			
DRIVE TRAIN						
Transmission	HST - 2 range		Synchro Mesh		HST - 2 range	
Number of Speeds	Infinite		6F/2R		Infinite	
Clutch	Dry-Single					
Brakes	Wet Disc					
PTO						
Type	Independent		Trans		Independent	
Rear PTO RPM	540 @ 2942		540 @ 2893		540 @ 2550	
Mid PTO RPM	2500 @ 2958		2000 @ 2875		2000 @ 2550	
PTO HP (kW)	14.2 (10.6)		15.9 (11.8)		16.9 (12.26)	
HYDRAULICS						
Type	Open Center					
Implement Pump Output [gpm (L/min)]	4.1 (15.5)		4.5 (17.0)			
Maximum Total Flow [gpm (L/min)]	6.2 (23.4)		7.1 (26.9)			
3-Point Hitch	CAT I Narrow with Check Chains		CAT I with Check Chains			
Lift Capacity [lb (kg)]	680 (309)		1323 (600)			
ELECTRICAL						
Battery	12 V, 450 CCA					
Alternator	12 V, 45 A		12 V, 50 A			
DIMENSIONS						
Overall Length [in (mm)]	94.2 (2392)		100.5 (2552)			
Overall Width [in (mm)]	44.5 (1130)		45.8 (1164)			
Overall Height [in (mm)]	86.6 (2299)	79.6 (2023)	91.3 (2320)		78.2 (1986)	
Wheelbase [in (mm)]	53.1 (1348)		57.5 (1460)			
Minimum Ground Clearance [in (mm)]	8.3 (210)		9.4 (240)			
Turning Radius [ft (m)]	7.2 (2.1)					
Weight [lb (kg)]	1499 (679.9)	1800 (817)	1638 (742)		1870 (850)	
WHEELS & TIRES						
AG [Front/Rear]	18 x 8.5-10 / 26 x 12-12		6x12 / 9.5x16			
IND [Front/Rear]	18 x 8.5-10 / 26 x 12-12		20x18-10 / 27 x 12.5-15			
TURF [Front/Rear]	18 x 8.5-10 / 26 x 12-12		20 x 8-10 / 29 x 12.5-15			