

# **PERFORMANCE BULLETIN**



# **SEA FOX® 328 COMMANDER**

Length	32' 0"
Beam	10' 8"
Dry Weight (Boat Mfr. Pub)	8,975 lbs
Maximum HP	700 hp
Fuel Capacity	311 gal
Weight as Tested	12,245 lbs

### F350UCC / LF350UCC

Horsepower	350 hp
Induction	EFI
Displacement	5.3 L
Weight (Estimated)	780 - 780 lbs
Gear Ratio	1.73

### **ENGINE MOUNTING HEIGHT**

Mounting Hole Position	#2
Ventilation Plate Height	1/2" Above Boat Bottom

## PROPELLER(S)

Series	Saltwater Series XL®
Diameter x Pitch	15 1/2 x 19
Yamaha Part #	6AW-45974-20-00 / 6AX-45974-20-00
Propeller Material	Polished Stainless Steel

### **TEST CONDITIONS**

Number of People	2
Air / Water Temperature	78° F / 82° F
(Fahrenheit)	76 1762 1
Elevation (in feet above sea level)	0'
Wind Velocity	5-10 MPH

# **COMMENTS**

Test weight includes 1/2 tank of fuel, 6 batteries, safety and test gear.

YPB#: PB\_SFX\_328Commander\_t\_F350UCC\_2017-01-24\_OCC



Engine: Yamaha F350UCC / LF350UCC

**Boat:** Sea Fox® 328 Commander

**Configuration:** Twin **Test Date:** 24-Jan-2017



## **PERFORMANCE DATA**

RPM	МРН	GPH	MPG
1000	5.5	3.3	1.67
1500	8.2	5.6	1.46
2000	9.5	9.5	1
2500	14	13.8	1.02
3000	21.6	18.3	1.18
3500	32.6	21.7	1.5
4000	37.3	26.5	1.41
4500	42.3	33.2	1.27
5000	47.5	41.6	1.14
5500	52.9	56.7	0.93
6000	57.3	65.5	0.88
0-30 MPH : 5.75			

NOTICE TO CONSUMER

The information and data contained in this Performance Bulletin is approximate and subject to many different factors and variables. It is provided as a guideline only and should not be relied upon as representative of actual performance. Your boat's performance may be different than the information contained in this Performance Bulletin due to various factors, including your boats sactual weight, wind and water conditions, temperature, humidity, elevation, bottom paint, boat options affecting wind/water drag and/or boat weight, and operator ability, Please confirm the specifications and performance data on your specific boat/reging combination with your dealer prior to purchase. Please also keep in mind that the data contained in this Performance Bulletin may or may not have been performed using Yamaha Persevers the right to change the specifications and performance data of this Performance Bulletin or engine without notice. This document contains many of Yamaha's valuable trademarks. It may also contain trademarks belonging to other companies. Any references to other companies or their products are for identification purposes only, and are not intended to be an endorsement.