



### SIMPLE AND EFFECTIVE

With the Typhoon™, you can instantly decide to go out boating: light and compact, it easily fits in the boot of your car.

### THE “+” of the PRODUCT

A removable inflatable floor: inflated at high pressure, it is as rigid and less heavy than a traditional floor! An inflatable keel: it ensures a good heading hold and provides an extra buoyancy. Semi-recessed valve and swimming platform.

### TECHNICAL FEATURES

EXTERNAL LENGTH (m-ft)	4.2 - 13'9"	AVERAGE RECOMMENDED POWER (kW)	12
INSIDE LENGTH (m-ft)	2.8 - 9'2"	MAXIMUM AUTHORIZED POWER (HP)	25
OVERALL BEAM (m-ft)	1.9 - 6'3"	MAXIMUM AUTHORIZED POWER (kW)	19
INSIDE BEAM (m-ft)	0.92 - 3'0"	MAXIMUM AUTHORIZED ENGINE WEIGHT (Kg-Lbs)	72 - 158
FLOAT DIAMETER (m-ft)	0.49 - 1'7"	MAXIMUM SPEED (MONO) (km/h - mph)	40-25
NUMBER OF PASSENGERS (ISO)	7	HULL LENGTH AT THE 1st BAG (tube) (m - ft)	1.3 - 4'3"
MAXIMUM AUTHORIZED LOAD (Kg-Lbs)	750 - 1653	HULL WIDTH AT THE 1st BAG (tube) (m - ft)	0.75 - 2'6"
TOTAL WEIGHT (Kg-Lbs)	85 - 187	HULL HEIGHT AT THE 1st BAG (Tube) (m - ft)	0.3 - 0'12"
NUMBER OF WATERTIGHT COMPARTMENTS	5+1	LENGTH OF THE 2nd BAG (floor) (m - ft)	1.2 - 3'1"
DESIGN CATEGORY	C	WIDTH OF THE 2nd BAG (floor) (m - ft)	0.8 - 2'7"
SHAFT	S	HEIGHT OF THE 2nd BAG (Floor) (m - ft)	0.16 - 0'6"
AVERAGE RECOMMENDED POWER (HP)	15		

### VERSIONS

420 ALU



OPTIONS

**HULL & DECK**  
Side rigid ladder

**OTHER(S)**  
Launching wheels

Pressure indicator valve bravo 5

**Taxes**  
Eco contribution France 4 à 4,99m pneumatiques