

BIGDOG
— MOWER CO. —

ALPHA

— SERIES —



ALPHA

AVAILABLE DECK SIZES

36" - 52"



ALPHA MP

AVAILABLE DECK SIZES

36" - 60"



ALPHA MPX

AVAILABLE DECK SIZES

48" - 60"

ALPHA

7 YEAR RESIDENTIAL WARRANTY
INDUSTRY LEADING LIMITED OR **300** HOUR

Fabricated Frame for Durability

1.50" x 3.25" steel frame making it one of the toughest and most durable in its class.

Welded Steel Deck

Durable 11 ga. welded fabricated steel deck adds durability, prevents rusting, & extends mower's life (compared to other brand's cheap stamped decks).

Precision Steering

Precision control to help trim and maneuver easily around obstacles. Other brands have sensitive steering arms causing sudden and jerky movements.

Premium Seat

With built-in lumbar support and natural air flow.

Briggs & Stratton PXi Engine

18, 20, 23hp

Foot Operated Deck Lift

Easily adjust the deck height between 1.5" - 4.5" with less effort than hand-operated levers found on other brands.

18" BigBite™ Tires

For a smooth ride and enhanced traction.

IDEAL FOR UP TO

1
ACRE





ACCESSORIES

- Mulch Kit
- 2-Bag Catcher (Alpha MPX only)
- Side Steel Catcher (4.4 cu ft, Alpha MPX only)
- Side Mesh Catcher (3 bu, Alpha MPX only)
- Steering Extension Kit
- Flex Forks
- Stripe Kit
- Always-On LED Light Kit

UPGRADES FOUND ON THE ALPHA MP AND ALPHA MPX

ALPHA MP

Compared to Alpha

- Higher-Back Seat with Armrests
- Increased Deck Depth (4.5")
- Larger Transmissions (Hydro-Gear ZT-2800®)
- Larger 20" BigBite Tires
- Additional Horsepower
- Larger 13" Front Caster Tires



ALPHA MPX

Compared to Alpha MP

- Extra High-Back Seat with Armrests
- Increased Deck Depth (5"), and deck thickness (10 ga)
- Larger 22" BigBite Tires
- Larger Transmissions (Hydro-Gear ZT-3100®)



ALPHA SERIES

	ALPHA	ALPHA MP	ALPHA MPX
ENGINE			
Manufacturer	Briggs & Stratton PXI series		Briggs & Stratton Commercial series
HP	36": 18HP 42": 20HP 52": 23HP (Per SAE J1995)	36", 42" : 20HP 48", 54": 23HP 60": 25HP (Per SAE J1995)	48", 54": 23HP 60": 25HP (Per SAE J1995)
Displacement	36": 656cc 42": 656cc 52": 724cc	36", 42": 656cc 48", 54", 60": 724cc	724cc
Cooling	Air cooled		
Engine Warranty	3 year		
DRIVE SYSTEM			
Type	Dual hydrostatic		
Transmission	36" & 42" decks: Hydro-Gear ZT-2100 52" deck: Hydro-Gear ZT-2200	Hydro-Gear ZT-2800	Hydro-Gear ZT-3100
Speed	Up to 6.5 mph	Up to 7.5 mph	Up to 7 mph
Parking Brakes	Integrated with steering levers		
DECKS			
Cutting Width	36", 42", 52"	36", 42", 48", 54", 60"	48", 54", 60"
Cutting Heights	1.5" - 4.5"		
Deck Lift	Foot operated		
Depth	4.1"	4.5"	5"
Blades	36", 42": 2 52": 3	36", 42": 2 48", 54", 60": 3	3
Blade Tip Speed	36": 18,600 42": 16,700 52": 16,600	36", 42", 60": 18,400" 48": 18,600" 54": 18,900	48": 18,600 54": 18,900 60": 18,400
Blade Length	36", 52": 17.86" 42": 20.50"	36" Deck: 17.86" 42" Deck: 20.50" 48" Deck: 16.50" 54" Deck: 18.50" 60" Deck: 20.50"	48": 16.50" 54": 18.50" 60": 20.50"
Spindles	Aluminum with 3/4" shafts and triple protection sealed ball bearings	Aluminum with 1" steel shafts and sealed ball bearings	Aluminum with 1" shafts and sealed ball bearings
Drive	Electric PTO clutch		
Construction	11 ga. fabricated	11 ga. fabricated	10 ga. fabricated
Spindle Mounts	Reinforced 14 ga.	Reinforced 7 ga.	Stamped spindle cans 11 ga.
Impact/Trim Areas	1/4" x 3/4" steel bar	3/8" x 1" steel bar	3/8" x 1" steel bar
CONSTRUCTION			
Frame	1.5" x 3.25" steel C-channel	1.5" x 3.25" 11 ga. steel C-channel	1.5" x 3.25" steel C-channel
Front Axle	Fabricated with sealed ball bearings		
Front Caster Wheels	Sealed ball bearings		
Front Caster Forks	Fabricated 1/4" steel	Fabricated 3/8" steel	Fabricated .375" steel
GENERAL			
Seat	Mid back seat with suspension springs	Premium high back seat with armrests and suspension springs	Premium extra high back seat with armrests and suspension springs
Fuel Capacity	3 gallons	3 gallons	3 gallons
Cup Holder	Yes	Yes	Yes
Front Tire	36", 42": 11 x 4, Smooth tread 52": 11 x 6, Smooth tread	36", 42", 48": 13 x 5, Smooth tread 54", 60": 13 x 6.5, Smooth tread	48": 13 x 5, Smooth tread 54", 60": 13 x 6.5, Smooth tread
Drive Tire	36": 18 x 7 - 8, BigBite 42", 52": 18 x 8.5 - 8, BigBite	36", 42": 20 x 6.5 - 10, BigBite 48": 20 x 8 - 10, BigBite 54", 60": 20 x 12 - 10, BigBite	48": 22 x 9.5 - 10, BigBite 54", 60": 22 x 11 - 10, BigBite
DIMENSIONS			
Weight	36": 465 lbs 42": 495 lbs 52": 515 lbs	36": 577 lbs 42": 587 lbs 48": 625 lbs 54": 650 lbs 60": 670 lbs	48": 620 lbs 52": 666 lbs 60": 671 lbs
Height	39"		
Length	73"		
Width w/Chute Up	36": 38.3" 42": 44.4" 52": 53.4"	36": 37.3" 42": 44.4" 48": 49.7" 54": 55.7" 60": 61.7"	48": 49" 54": 55" 60": 61"
Tire Width	36": 37.7" 42", 52": 41"	36", 42": 38.3" 48": 41.3" 54", 60": 47.8"	48": 43.8" 54", 60": 47.7"
Trim Side	36": 0" 42": 0.3" 52": 6.8"	36": 0 42": 1.9" 48": 3.7" 54": 3.4 60": 6.4"	48": 2.9" 54": 3.8 60": 7.9"
PRODUCTIVITY*			
Acres Per Hour	36": 1.89 42": 2.2 52": 2.72	36": 2.18 42": 2.54 48": 2.91 54": 3.27 60": 3.64	48": 2.91 54": 3.27 60": 3.64

* Number based on 80% efficiency. This rating is to account for actual mowing conditions including overlapping, turning and terrain.

** Specifications are subject to change without notice.