



DASH XD

AVAILABLE DECK SIZES

Engine	Deck Sizes
15HP* - Kawasaki® FR541	34", 42"
18HP* - Kawasaki® FR600	48"



DASH XD

IDEAL FOR UP TO

1
ACRE¹

Fabricated Steel Frame
1"x2" fabricated steel frame making it tough and durable.

Foot Operated Deck Lift
Easily adjust the deck height between 1.5" - 4.5".

Welded Fabricated Steel Deck
11 ga. welded fabricated steel deck adds durability compared to a stamped deck.

Bolstered Seat
Bolstered with built-in lumbar support.

18" BigBite™ Rear Tires
We worked directly with the tire manufacturer on this design.

Compact Size
Easily fits through most gates help making backyard mowing easy and ideal for garage storage.

Kawasaki® Power
V-Twin Kawasaki® engine

LIMITED
WARRANTY

2 YEAR | **200** HOUR

RESIDENTIAL



Standard Engine Guard





FEATURES FOUND ON THE DASH

DASH XD

IDEAL FOR UP TO

1
ACRE¹

- ✓ **18" BigBite™ Rear Tires**
- ✓ **Standard Engine Guard**
- ✓ **Kawasaki® Power V-Twin Kawasaki® engine**
- ✓ **Compact Size**
Easily fits through most gates help making backyard mowing easy and ideal for garage storage.



ACCESSORIES

(Each sold separately)

- ▶ Mulch kit
- ▶ Grass bagger (non-powered 2.0 bushels)
- ▶ Steering lever extension kit
- ▶ Light kit
- ▶ Armrest kit
- ▶ Stripe kit

LIMITED
WARRANTY

2 YEAR | **200** HOUR

RESIDENTIAL

DASH XD

ENGINE	
Manufacturer	Kawasaki® FR series
HP	34" & 42" deck: 15HP* - FR541 48" deck: 18HP* - FR600 (Per SAE J1995)
Displacement	603cc
DRIVE SYSTEM	
Type	Dual hydrostatic
Transmission	Hydro-Gear® ZT-1800®
Speed	Up to 6 mph
Parking Brakes	Integrated with steering levers
DECKS	
Cutting Width	Side discharge: 34", 42", 48"
Cutting Heights	1.5" - 4.5"
Deck Lift	Foot operated
Depth	4.1"
Blades	34" & 42": 2 • 48": 3
Blade Length	34": 16.75" 42": 20.50" 48": 16.5"
Blade Tip Speed	34": 17,500 • 42": 16,700 48": 17,200
Spindles	Aluminum with 3/4" shafts and triple protection sealed ball bearings
Drive	Electric PTO clutch
Construction	Fabricated 11 ga. steel
Spindle Mounts	Reinforced 14 ga. steel
Impact/Trim Areas	1/4" x 3/4" steel bar
CONSTRUCTION	
Frame	1" x 2" steel tubing
Front Axle	Fabricated with sealed ball bearings
Front Caster Wheels	Sealed ball bearings
Front Caster Forks	Fabricated 1/4" steel
GENERAL	
Seat	Bolstered seat with built-in lumbar support
Fuel Capacity	2 gallons
Cupholder	Yes
Front Tire	11 x 4
Drive Tire	34": 18 x 6.5 - 8 BigBite™ • 42", 48": 18 x 8.5 - 8 BigBite™
DIMENSIONS	
Weight	34" deck: 455 lbs • 42" deck: 467 lbs • 48" deck: 490 lbs
Height	40"
Length	65.4"
Width w/Chute	34": 37.5" • 42": 43.25" • 48": 48.25"
Tire Width	34": 35" • 42", 48": 41"
Trim Side	34": 0.4" • 42": 0.3" • 48": 4.1"
PRODUCTIVITY**	
Acres Per Hour	34": 1.65 • 42": 2.04 • 48": 2.33

Specifications are subject to change without notice.

¹ Guidance and recommendations based on total property size and will vary depending on yard and terrain conditions. See your local dealer for expert advice.

* As rated by the engine manufacturer.

** Number based on 80% efficiency. This rating is to account for actual mowing conditions including overlapping, turning and terrain.

Kawasaki is a registered trademark owned by KAWASAKI JUKOGYO KABUSHIKI KAISHA. Vanguard is a registered trademark owned by Briggs & Stratton Corporation.

Hydro-Gear is a registered trademark owned by Hydro-Gear Limited Partnership.