

Kawasaki





## STRONG. TOUGH. RELIABLE. KAWASAKI TO ITS CORE.

## BRUTE FORCE 750 4x4i

The sporty yet rugged styling of the Brute Force 750 4x4i and 4x4i EPS is not just skin deep. Under the aggressive bodywork is a liquid-cooled, fuel-injected 749cc, 90-degree V-twin and a reinforced double-cradle frame for optimum rough trail handling. Matched by responsive independent double A-arm suspension on all four wheels, the result is light, easy handling that puts the emphasis of this sport-utility ATV decidedly on sport. The 2016 Kawasaki Brute Force 750 4x4i is your ticket to ride. Anywhere. Anytime. Kawasaki Strong.

## NEXT GENERATION FUEL-INJECTED V-TWIN ENGINE

ON-DEMAND VARIABLE FRONT DIFFERENTIAL CONTROL

HIGHLY ACCLAIMED SEALED INTERNAL WET REAR BRAKE

ELECTRICALLY SELECTABLE 2WD/4WD

HIGH-GRADE ELECTRIC POWER STEERING (EPS) AVAILABLE







750 4x4i EPS 750 4x4i





## PLENTY OF RIDING EXCITEMENT COMBINED WITH EVERYDAY VERSATILITY.

22UTE FORCE 300

Don't sweat the long days. Let the Brute Force 300 do it for you. Whether you have orchards to tend to, livestock to feed, or trails to clear, you can make it happen with this eager ATV. It has the power and towing capacity to get stuff done and have fun doing it. An incredibly strong, durable, heavy-duty steel-tube frame promotes superb handling and straight-line stability. A broad stance and long A-arms give the Brute Force 300 an extremely predictable and stable ride, so every rider can relish even the most challenging routes.

PROVEN 271cc LIQUID-COOLED, 4-STROKE SINGLE ENGINE

CVT TRANSMISSION WITH CENTRIFUGAL CLUTCH

TRIPLE DISC BRAKES OFFER STRONG STOPPING POWER AND GOOD BRAKE FEEL

SPORTY-HANDLING CHASSIS DESIGNED TO OFFER HIGH STRAIGHT-LINE STABILITY AND CORNERING ABILITY

SUBTANTIAL 500 LB (227 KG) TOWING CAPACITY

THICK-CUSHION SEAT PROVIDES ALL-DAY RIDING COMFORT

CONVENIENT FRONT AND SIDE STORAGE SPACE

HANDY DC ACCESSORY OUTLET

12L FUEL TANK OFFERS GOOD RANGE





300





# FULLY AUTOMATIC TRANSMISSION, FULL SUSPENSION AND RUGGED STYLING



Getting any young rider off to a great start is easy with the 2016 KFX50 with a smooth yet potent four-stroke 49cc single engine. When a young rider is ready for a little more power, the KFX90 steps into the spotlight. Powered by an 89cc four-stroke single, the 2016 KFX 90 has enough power to be a lot of fun, but not so much that it intimidates a developing rider. Adding to rider comfort and a secure, incontrol feeling are full floorboards, keeping feet in contact with the ATV whether standing up or sitting down. Electric start is a confidence building feature; just squeeze the brakes, push the button and the KFX starts up.

ELECTRIC START WITH KICK-START BACKUP

REAR HYDRAULIC DRILLED DISC BRAKE

INDEPENDENT A-ARM FRONT SUSPENSION WITH PRELOAD ADJUSTABLE SHOCKS

CONTINUOUSLY VARIABLE TRANSMISSION (CVT)

KEYED IGNITION SWITCH PREVENTS STARTING WITHOUT A KEY

EASY-TO-USE PARENTAL CONTROLS FOR SETTING SPEED AND POWER LIMITS

IGNITION CUT-OFF LANYARD SAFETY SWITCH

WIDE STANCE FOR CONFIDENT HANDLING IN THE TRAILS





KFX 90

KFX 50



## CUSTOMISE WITH KAWASAKI GENUINE ACCESSORIES.



#### **DEVELOPED BY KAWASAKI ATV ENGINEERS**

This ensures a perfectly integrated fit, an easy, seamless installation, and long-lasting dependability.



#### THOROUGHLY TESTED

Through exhaustive testing by Kawasaki engineers, these accessories meet the same stringent quality standards as every Kawasaki Strong ATV.



#### WARRANTY COMPLIANT

Kawasaki Genuine Accessories never compromise the status of your standard Kawasaki Warranty.

### ALL-WEATHER



### COMFORT



### PROTECTION









STORAGE UTILITY

HUNTING



	BRUTE FORCE™ 750 4x4i EPS / SE	BRUTE FORCE™ 300	KFX <sup>™</sup> 90	KFX™50
Engine type	Liquid-cooled, 4-stroke, 90° V-Twin	Liquid-cooled, 4-stroke, Single	Forced air-cooled, 4-stroke Single	Forced air-cooled, 4-stroke Single
Displacement	749cc	271cc	89.9cc	49.5cc
Bore x stroke	85 x 66 mm	72.7 x 65.2 mm	47.0 x 51.8 mm	39.0 x 41.4 mm
Compression Ratio	9.3:1	11.0:1	10.0:1	10.8:1
Valve system	SOHC, 4 valves per cylinder	SOHC, 2 valves per cylinder	SOHC, 2 valves per cylinder	SOHC, 2 valves per cylinder
Fuel system	Digital fuel injection with dual 36 mm throttle bodies	CVK32 carburettor	Keihin PTE 16 carburettor	Keihin PTE 16 carburettor
Ignition	Digital DC-CDI	Full transistor digital ignitiion	CDI	CDI
Starting	Electric	Electric with recoil backup	Electric with kick back-up	Electric with kick back-up
Transmission	Dual range CVT with reverse	Dual range CVT with reverse	Automatic, CVT with centrifugal clutch	Automatic, CVT with centrifugal clutch
Final drive	Shaft, Electric 2WD/4WD, rider controlled locking front differential	Shaft 2WD	Chain	Chain
Frame type	Double cradle, high-tensile tubular steel	Double cradle, high-tensile tubular steel	Double cradle, tubular steel	Double cradle, tubular steel
Front suspension	Double wishbone with 5-way adjustable spring preload	Double wishbone with 5-way adjustable preload	Single A-arm with twin shocks	Independent, single A-arm with twin shocks
Rear suspension	Double wishbone with 5-way adjustable spring preload	Swingarm with 5-way adjustable preload	Uni-Trak Swingarm, single shock	Uni-Trak Swingarm, single shock
Wheel travel,front/rear	169/190 mm (6.5/7.5 in.)	131/141 mm (5.2/5.6 in.)	71/74 mm (2.8/2.9 in.)	71/74 mm (2.8/2.9 in.)
Tires, front/rear	Tubeless: AT 25 x 8-12 / AT 25 x 10-12	MAXXIS: AT 22 x 7-10 / AT 22 x 10-10	AT 18 x 7-8/AT 18 x 9-8	AT 16 x 8-7/AT 16 x 8-7
Brake type, front/rear	Dual hydraulic drilled discs with twin-piston calipers/ Enclosed wet multi-plate	Dual 180 mm discs with single-piston calipers/ 180 mm disc with single-piston caliper	Dual mechanical drums/ Single hydraulic disc	Dual mechanical drums/ Single hydraulic disc
Dimensions (LxWxH)	2195 x 1180 x 1220 mm (86.4 x 46.5 x 48 in.)	1915 x 1080 x 1170 mm (74.4 x 42.5 x 46.1 in.)	1425 x 905 x 925 mm (56.1 x 35.6 x 36.4 in.)	1400 x 880 x 910 mm (55.1 x 34.7 x 35.8 in.)
Seat height	910 mm (35.8 in.)	845 mm (33.4 in.)	650 mm (25.6 in.)	635 mm (25.0 in.)
Ground clearance	240 mm (9.5 in.)	155 mm (6.1 in.) (at rear case guard)	100 mm (3.9 in.) (center of chassis)	85 mm (3.35 in.)
Fuel capacity	19 litres (4.2 gal.)	12 litres (2.6 gal.)	5.5 litres (1.2 gal.)	5.5 litres (1.2 gal.)
Instrumentation	Speedometer, odometer, tripmeter, fuel gauge, engine temperature indicator, clock and hour meter, indicator lamps for EPS (EPS model only), neutral, reverse gear, 2WD/4WD, belt indicator, and oil warning	Speedometer, odometer, clock, fuel gauge and coolant temperature light	N/A	N/A
Curb mass*	315 kg (694.4 lbs.) <b>4x4i</b> : 310 kg (683 lbs.)	243 kg (535.4 lbs.)	121 kg (266.8 lbs.)	111 kg (244.7 lbs.)
Colours	Bright White, Candy Lime Green (Special Edition), Camouflage Realtree® Xtra® Green <b>4x4i:</b> Timberline Green	Super Black or Bright White	Lime Green	Lime Green
Warranty	12 months	12 months	12 months	12 months

<sup>\*</sup> Includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90% of capacity) and tool kit (if supplied)

#### KAWASAKI CARES

Warning: ATVs can be hazardous to operate. For your safety: Always wear a helmet, eye protection, and protective clothing. Never carry a passenger. Never ride under

the influence of drugs or alcohol. Never ride on public roads or pavement. Avoid excessive speeds and stunt driving. Be extra careful on difficult terrain. Kawasaki ATVs with engines over 90cc are recommended for use only by persons 16 years

of age or older. Kawasaki also recommends that all ATV riders take a training course. For more information, see your dealer, or call the Canada Safety Council at 1-613-739-1535 ext. 233.



Kawasaki