



DK20 Series Specifications

MODEL		DK4520	DK5020	DK5520
ENGINE				
Engine Gross	HP (KW)	44.9 (33.5)	50.3 (37.5)	55 (41)
PTO	HP (KW)	38.9 (29.0)	41.5 (31.0)	46.4 (34.6)
Displacement	cu. in. (cc)	111.4 (1,826)		
Rated Revolution		2,600 rpm		
Fuel Tank Capacity		11.9 gal. (45 ℓ)		
DRIVE TRAIN				
Clutch		Dry Single Stage		
Transmission		Synchronized Shuttle		
Speeds		8F/8R		
Differential Lock		Rear Standard		
Brake		Wet Disc Type		
PTO		Independent		
Rear PTO (Standard)		540 rpm		
Mid PTO (Optional)		N/A		
4WD Type		Manual		
HYDRAULIC SYSTEM				
Pump		Gear		
Pump Capacity (Max flow rate)		14.56 gpm (55.1 ℓpm)		
3-Point Hitch		Category I		Category II
Maximum Lifting Capacity*		2,716 lbs. (1,232 kg)		
Hydraulic Lift Control System		Position		
No. of Standard Remote Valves		(2 Optional)		
Steering		Hydraulic Power Steering		
TIRE SIZE				
Front AG. (Turf, Industrial)		8-16 (29-12.5-15, 10-16.5)		
Rear AG. (Turf, Industrial)		13.6-24 (21.5L-16.1, 14.9-24)		
TRAVELING SPEEDS				
Forward	mph (kph)	1.29~16.71 (2.08~26.9)		
Reverse	mph (kph)	1.26~16.28 (2.03~26.2)		
DIMENSIONS				
Overall Length (incl. 3-pt hitch)		124.3 in. (3,157 mm)		
Overall Width (min. tread)		62.8 in. (1,596 mm)		
Overall Height		96.8 in. (2,458 mm)		
Wheelbase		71.3 in. (1,810mm)		
Min. Ground Clearance		14.5 in. (368 mm)		
Tread	Front (AG)	49.4 in. (1,254 mm)		
	Rear (AG)	49.3 in. (1,251 mm)		
Min. Turning Radius (w/brake)		102.8 ft. (2,610 mm)		
Weight w/AG. Tires	lbs. (kg)	3,373 (1,530)		

*(24" aft. of hitch)

NOTE: Specifications and design are subject to change without notice.

STANDARD EQUIPMENT

- Power Steering
- Rear PTO
- Wet Multi Disc Brakes
- Drawbar
- Headlights
- Parking Brake
- PTO Shield

OPTIONAL EQUIPMENT

- Front Weights
- Deck Mat
- Clevis Type Drawbar
- Side View Mirror (1 ea / ROPS Only)
- Fuel Heater Kit
- Single Remote Hydraulic Valve (Spring/Detent)
- 2nd Remote Hydraulic Valve (Spring/Detent)
- Rear Wheel Weight (Ag & Ind Tires Only)
- 3rd Function Kit for Loader
- Bluetooth Speaker Kit
- RPM Increase Kit for Loader

ATTACHMENTS

- Front End Loader
- Backhoe
- Snowblower
- Contact your local KIOTI dealer for available implements and attachments.

KIOTI.com



DK20SE Series Specifications

MODEL	DK4220SEH	DK4220SEH CAB	DK4720SEH	DK4720SEH CAB	DK5320HSE	DK5320HSE CAB	DK6020HSE	DK6020HSE CAB	
ENGINE									
Engine Gross	HP (KW)	39.6 (29.5)		44.9 (33.5)		50.3 (37.5)		57.7 (43)	
PTO	HP (KW)	29.1 (21.7)		33.4 (24.9)		39.3 (29.3)		44.9 (33.5)	
Displacement	cu. in. (cc)	1,826 (111.4)							
Rated Revolution		2,600 rpm							
Fuel Tank Capacity		12.7 gal. (39.6 ℓ)							
DRIVE TRAIN									
Clutch		N/A							
Transmission		HST							
Speeds		3 Range							
Differential Lock		Rear Standard							
Brake		Wet Disc Type							
PTO		Independent							
Rear PTO (Standard)		540 rpm							
Mid PTO (Optional)		2,000 (Optional)							
4WD Type		Manual							
HYDRAULIC SYSTEM									
Pump		Gear							
Pump Capacity (Max flow rate)		16.49 gpm (62.4 ℓpm)							
3-Point Hitch		Category I				Category II			
Maximum Lifting Capacity*		2,716 lbs. (1,232 kg)							
Hydraulic Lift Control System		Position							
No. of Standard Remote Valves		2							
Steering		Hydraulic Power Steering							
TIRE SIZE									
Front AG. (Turf, Industrial)		8-16 (29-12.5-15, 10-16.5)							
Rear AG. (Turf, Industrial)		13.6-24 (21.5L-16.1, 14.9-24)							
TRAVELING SPEEDS									
Forward	mph (kph)	0~18.45 (0~29.7)							
Reverse	mph (kph)	0~12.92 (0~20.8)							
DIMENSIONS									
Overall Length (incl. 3-pt hitch)		125.5 in. (3,189 mm)							
Overall Width (min. tread)		62.8 in. (1,596 mm)							
Overall Height		96.8 in. (2,458 mm)	93 in. (2,363 mm)	96.8 in. (2,458 mm)	93 in. (2,363 mm)	96.8 in. (2,458 mm)	93 in. (2,363 mm)	96.8 in. (2,458 mm)	93 in. (2,363 mm)
Wheelbase		71.3 in. (1,810 mm)							
Min. Ground Clearance		14.5 in. (368 mm)							
Tread	Front (AG)	49.4 in. (1,254 mm)							
	Rear (AG)	49.03 in. (1,251 mm)							
Min. Turning Radius (w/brake)		102.8 ft. (2,610 mm)							
Weight w/AG. Tires	lbs. (kg)	3,523 (1,598)	4,043 (1,834)	3,523 (1,598)	4,043 (1,826)	3,523 (1,598)	4,043 (1,826)	3,523 (1,598)	4,043 (1,826)

*(24" aft. of hitch)

NOTE: Specifications and design are subject to change without notice.

STANDARD EQUIPMENT

- Power Steering
- Rear PTO
- Dual Remote Hydraulic Valve (Spring/Detent)
- Wet Multi Disc Brakes
- Joystick Valve
- Drawbar
- Front Working Lights (Cab)
- Rear Working Light (Cab)
- Headlights
- Parking Brake
- PTO Shield

OPTIONAL EQUIPMENT

- Beacon Light
- Front Weights
- Mid PTO
- HST Linked Pedal
- Fuel Heater Kit
- Rear Wheel Weight (Ag and Ind Tires Only)
- 3rd Function Kit for Loader
- RPM Increase Kit for Loader
- Bluetooth Speaker Kit (ROPS Only)
- Clevis Type Drawbar
- Side View Mirror (1 ea / ROPS Only)

ATTACHMENTS

- Front End Loader
- Backhoe
- Snowblower
- Contact your local KIOTI dealer for available implements and attachments.

KIOTI.com