



HEAVY-DUTY STRAIGHT-BLADE

APPLICATIONS: MEDIUM-DUTY TRUCKS 14,000-27,000 GVWR



SPECIFICATIONS	9' Heavy-Duty (Steel)	10' Heavy-Duty (Steel)
Blade Width (Straight)	108" (274 cm)	120" (305 cm)
Plowing Width @ 30° Angle	94" (239 cm)	104" (264 cm)
Blade Height	34-1/2" (88 cm)	34-1/2" (88 cm)
Blade Thickness	7-ga steel	7-ga steel
Cutting Edge (High Performance)	1/2" x 6" (1.3 cm x 15 cm)	1/2" x 6" (1.3 cm x 15 cm)
Reinforcement Ribs	8 vertical, 2 diagonal	8 vertical, 2 diagonal
Plow Shoes	Cast Iron	Cast Iron
Trip Springs	6	6
Angle Cylinders	2" x 10" (5 cm x 25 cm)	2" x 10" (5 cm x 25 cm)
Lift Cylinder	2-1/4" x 1-1/8" x 12" (6 cm x 3 cm x 31 cm)	2-1/4" x 1-1/8" x 12" (6 cm x 3 cm x 31 cm)
Shock Absorber	2	2
Attachment System	SmartHitch 2	SmartHitch 2
Plow Weight*	1152 lb (523 kg)	1205 lb (547 kg)
Plow Lights	SL3 L.E.D. with Ice Shield Technology	SL3 L.E.D. with Ice Shield Technology

*Plow weight does not include vehicle mount weight. Vehicle mount weight range: 75-105 lb (34-48 kg).