



PRIMAVERA S 50 – TECHNICAL SPECIFICATIONS

| | |
|-----------------------------|---|
| ENGINE | Single cylinder 4-stroke, 3 valves, i-get Single cylinder |
| DISPLACEMENT | 49 cc |
| BORE X STROKE | 39 mm x 41,4 mm |
| MAX POWER AT | - |
| THE CRANK | |
| SHAFT | |
| MAX TORQUE | - |
| CONSUMPTION | - |
| CO2 EMISSIONS | - |
| COMPLIANCE | |
| FUEL SYSTEM | Electronic injection |
| COOLING | Forced air |
| STARTER | Electric |
| GEARBOX | CVT continuously variable transmission with torque server |
| CLUTCH | Automatic centrifugal dry clutch with vibration dampers |
| LOAD-BEARING | Sheet steel body with welded reinforcements |
| STRUCTURE | |
| FRONT | Single-sided link arm with coil spring and hydraulic monoshock absorber |
| SUSPENSION | |
| REAR | Coil spring with hydraulic monoshock absorber |
| SUSPENSION | |
| FRONT BRAKE | Ø 200 mm stainless steel disc with hydraulic control |
| REAR BRAKE | Ø 140 mm drum mechanically operated |
| ABS SYSTEM | - |
| FRONT TIRE | Tubeless 110/70 - 12" |
| REAR TIRE | Tubeless 120/70 - 12" |
| LENGTH / | - |
| WIDTH / WHEELBASE | |
| SEAT HEIGHT | 30.9 in |
| FUEL TANK CAPACITY | 1.9 gal |
| EMISSIONS COMPLIANCE | Euro 5 |