



SPRINT S 125 – TECHNICAL SPECIFICATIONS

ENGINE Single cylinder 4-stroke, 3 valves, i-get

DISPLACEMENT 124 cc

BORE X STROKE 52 mm x 58,6 mm

MAX POWER AT 8.1 kW - 11 HP - at 7.750 rpm

**THE CRANK
SHAFT**

MAX TORQUE 10.7 Nm at 6,250 rpm

CONSUMPTION 40 km/l

CO2 EMISSIONS 60 g/km

COMPLIANCE

FUEL SYSTEM Electronic injection

COOLING Forced air

STARTER Electric

GEARBOX CVT continuously variable transmission with torque server

CLUTCH Automatic centrifugal dry clutch with vibration dampers

LOAD-BEARING Sheet steel body with welded reinforcements

STRUCTURE

FRONT SUSPENSION Single-sided link arm with coil spring and hydraulic monoshock absorber

REAR SUSPENSION Coil spring with preload adjustable to 4 positions and hydraulic monoshock absorber

FRONT BRAKE Ø 200 mm stainless steel disc with hydraulic control

REAR BRAKE Ø 140 mm drum mechanically operated

ABS SYSTEM Single channel ABS

FRONT TYRE Tubeless 110/70 - 12"

REAR TYRE Tubeless 120/70 - 12"

LENGTH / 1,870 / 750 / 1,340 mm

WIDTH / WHEELBASE

SEAT HEIGHT 790 mm

FUEL TANK CAPACITY 8 litres

EMISSIONS COMPLIANCE Euro 5+