



SPRINT S 50 – TECHNICAL SPECIFICATIONS

ENGINE	Single cylinder 4-stroke, 3 valves, i-get
DISPLACEMENT	49 cc
BORE X STROKE	39 mm x 41,8 mm
MAX POWER AT	-
THE CRANK	
SHAFT	
MAX TORQUE	-
CONSUMPTION	-
CO2 EMISSIONS	-
COMPLIANCE	
FUEL SYSTEM	Electronic injection
COOLING	Forced air
STARTER	Electric
GEARBOX	CVT continuously variable transmission with torque server
CLUTCH	Automatic centrifugal dry clutch with vibration dampers
LOAD-BEARING	Sheet steel body with welded reinforcements
STRUCTURE	
FRONT	Single-sided link arm with coil spring and hydraulic monoshock absorber
SUSPENSION	
REAR	Coil spring with hydraulic monoshock absorber
SUSPENSION	
FRONT BRAKE	Ø 200 mm stainless steel disc with hydraulic control
REAR BRAKE	Ø 140 mm drum mechanically operated
ABS SYSTEM	-
FRONT TYRE	Tubeless 110/70 - 12"
REAR TYRE	Tubeless 120/70 - 12"
LENGTH /	-
WIDTH / WHEELBASE	
SEAT HEIGHT	31.1 in
FUEL TANK CAPACITY	2.0 gal
EMISSIONS COMPLIANCE	Euro 5