2026 MAVERICK X3 DS



PACKAGE HIGHLIGHTS

TURBO

- Smart-Lok™* front differential
 SHOWA HPG piggyback 2.5
- High torque Dynamic Power Steering
 (DDSTM)
- 30 in. XPS Trac Force tires
- 14 in. aluminum wheels
- 4.5 in. digital display with keypad
- Rear tow hook

TURBO RR

- Smart-Lok front differential
- SHOWA HPG piggyback 2.5
- High torque Dynamic Power Steering
 (DDS)
- Belt monitoring system
- 850 W magneto
- 30 in. XPS Trac Force tires
- 14 in. aluminum wheels
- · 4.5 in. digital display with keypad
- Rear tow hook

ENGINES	TURBO	TURBO RR
Туре	135 hp, Rotax* ACE (Advanced Combustion Efficiency) 900 cc turbocharged triple-cylinder engine, liquid-cooled and high-performance air filter	200 hp, Rotax ACE (Advanced Combustion Efficiency) 900 cc turbocharged triple-cylinder engine, liquid-cooled with integrated intercooler and high-performance air filter
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)	
Transmission	pDrive primary and Quick Response System X (QRS-X) CVT with high airflow, L / H / N / R / P	
Drive Train	Lockable front differential with exclusive Smart-Lok True 2WD/4WD with front diff. lock / 4WD TRAIL ACTIV / 4WD TRAIL	
Power Steering	High torque Tri-Mode Dynamic Power Steering (DPS)	
SUSPENSIONS		
Front Suspension	Arched double A-arm with sway bar / 20 in. (50.8 cm) suspension travel	
Front Shocks	SHOWA HPG piggyback 2.5 (dual-speed Compression, Dual-rate spring)	
Rear Suspension	4-link Torsional Trailing-arm X (TTX) with sway bar / 20 in. (50.8 cm) suspension travel	
Rear Shocks	SHOWA HPG piggyback 2.5 (dual-speed Compression, Dual-rate spring)	
TIRES & WHEELS		
Front / Rear Tires	XPS Trac Force 30 x 10 x 14 in.	
Wheels	14 in. cast-aluminum	
BRAKES		
Front	Dual 262 mm disc brakes with hydraulic twin-piston calipers	
Rear	Dual 248 mm disc brakes with hydraulic twin-piston calipers	

DIMENSIONS & CAPACITIES	TURBO	TURBO RR
Estimated Dry Weight	1,571 lb (713.3 kg)	
Chassis/Cage	Dual-phase 980 steel	
LxWxH	132 x 64 x 65.4 in. (335.3 x 162.5 x 166.1 cm)	
Wheelbase	102 in. (259.1 cm)	
Ground Clearance	14 in. (35.6 cm)	
Rack Capacity	200 lb (91 kg) with LinQ® quick-attach	
Storage Capacity	Total: 2.5 gal (9.4 L)	
Fuel Capacity	10.5 gal (40 L)	
FEATURES		
Gauge	4.5 in. digital display with keypad	
Instrumentation	DC outlet (10 A)	
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button	
Lighting	Premium high-performance LED headlights LED taillights	
Winch	N/A	
Magneto	650 W	850 W
Protection	Integrated front bumper Quarter-doors Full heavy-duty HMW plastic skid plate Rear tow hook	
WARRANTY & EXTEN	DED SERVICE	
Factory Warranty	1-year BRP limited warranty	
Extended Service Terms	B.E.S.T. term available up to 30 months	



