

TECHNICAL SPECIFICATIONS

2026 KTM 65 SX

ENGINE

Design	1-CYLINDER, 2-STROKE ENGINE
Displacement	64.9 CM³
Transmission	6-SPEED
EMS	MIKUNI VM 24
Engine oil	MOTOREX TOPSPEED 4T 15W50
Clutch primary drive teeth	75
Primary drive	23:75
Clutch	WET, MULTI-DISC CLUTCH, FORMULA HYDRAULICS
Engine cylinder	SINGLE CYLINDER
Engine stroke	2-STROKE

CHASSIS

Frame design	CENTRAL-TUBE FRAME WITH DOUBLE-CRADLE
Front brake	DISC BRAKE
Rear brake	DISC BRAKE
Rear subframe design	STEEL / POLYAMIDE GLASS FIBER
Chain	420

SUSPENSION

Front suspension	XACT 35 WP UPSIDE-DOWN FORK, Ø 35 MM
Rear suspension	XACT WP MONO SHOCK
Suspension travel (front)	215 MM
Suspension travel (rear)	253.5 MM
Front suspension adjustment	COMPRESSION AND REBOUND ADJUSTABLE
Rear suspension setting	COMPRESSION AND REBOUND ADJUSTABLE

DIMENSIONS

Seat height	730 MM
Ground clearance	259 MM
Tank capacity (approx.)	4.5 L
Weight (without fuel)	54.3 KG