



REGULAR WITH ROTARY DRUM	N92-310H	N92-312H	N98-310H	N98-312H
	N92-310HTR	N92-312HTR	N98-310HTR	N98-312HTR
Recommended horsepower (HP PTO)	85 @ 140	85 @ 140	85 @ 140	85 @ 140
Cutting width (in/mm)	92" 2337	92" 2337	98" 2489	98" 2489
Cutting height (in/mm)	38" 965	41 1/2" 1054	38" 965	41 1/2" 1054
Impeller RPM	540	540	540	540
Impeller diameter (in/mm)	31" 787	31" 787	31" 787	31" 787
Impeller depth (in/mm)	14 1/4" 362	14 1/4" 362	14 1/4" 362	14 1/4" 362
Number of blades	5	5	5	5
Impeller shaft diameter (in/mm)	2" 51	2" 51	2" 51	2" 51
Balanced impeller	Std	Std	Std	Std
Drum center height (in/mm)	19 1/2" 495	19 1/2" 495	19 1/2" 495	19 1/2" 495
Removable rotary drum	- / Std	- / Std	- / Std	- / Std
Chute rotation by hydraulic motor with valve (gear)	Std	Std	Std	Std
Hydraulic deflector	Std	Std	Std	Std
Manual deflector	Opt.	Opt.	Opt.	Opt.
Hydraulic cylinder for chute deflector (in/mm)	2 1/2" X 8" 64 X 203	2 1/2" X 8" 64 X 203	2 1/2" X 8" 64 X 203	2 1/2" X 8" 64 X 203
Semi-ind. chute (2 deflectors)	Std	Std	Std	Std
Hydraulic telescopic chute	Opt.	Opt.	Opt.	Opt.
Main auger diameter (in/mm)	23" 584	23" 584	23" 584	23" 584
Upper auger diameter (in/mm)	-	13" 330	-	13" 330
Balanced auger	Std	Std	Std	Std
Reversible carbon steel blade	Std	Std	Std	Std
Reversible Hardox 450 steel blade	Opt.	Opt.	Opt.	Opt.
Reversible stainless steel blade	Opt.	Opt.	Opt.	Opt.
Tivar blade	Opt.	Opt.	Opt.	Opt.
Lateral blades	Opt.	Opt.	Opt.	Opt.
Adjustable carbon steel skid shoes	Std	Std	Std	Std
Adjustable Hardox 450 steel skid shoes	Opt.	Opt.	Opt.	Opt.
Adjustable stainless steel skid shoes	Opt.	Opt.	Opt.	Opt.
Adjustable Tivar skid shoes	Opt.	Opt.	Opt.	Opt.
Hoses holder	Std	Std	Std	Std
Storage foot	Std	Std	Std	Std
Driving chain	80	80	80	80
Number of safety bolts	3	3	3	3
Bearing ductile iron casing	Std	Std	Std	Std
P.T.O. shaft (Std)	T80	T80	T80	T80
Box reducer 1 000 @ 540	Opt.	Opt.	Opt.	Opt.
Adjustable hitch	Std	Std	Std	Std
Hitch category (QH = quick hitch)	2, QH	2, QH	2, QH	2, QH
Approx weight (lb/kg) - 1 auger *	2105 / 955 2302 / 1044	2284 / 1036 2503 / 1135	2239 / 1016 2437 / 1105	2441 / 1107 2599 / 1179

*The weight includes the chute, the cylinder for chute deflector, the rotation kit and the PTO / Specifications subject to change without notice