



MATERIAL HANDLER

STANDARD FEATURES

- ◆ Discharge belt conveyor (pto driven)
- ◆ Walking floor chain conveyor in tub (hydraulic driven)
- ◆ Stainless steel floor in hopper
- ◆ Rear light kit
- ◆ Safety chains
- ◆ Re-capped truck tires

OPTIONS

- ◆ Bi-directional discharge conveyor with height adjustment (requires 3 sets of hydraulic outlets or diverter valve)
- ◆ Adjustable sand deflectors

Specifications:

	MH710	MH1216
Capacity (struck level)	7 cubic yards	12 cubic yards
Capacity (heaped)	10 cubic yards	16 cubic yards
Overall Height	86" (90" with bi-directional option)	97" (101" with bi-directional option)
Tub Length	143"	172"
Tub Depth	49"	60"
Overall Length	228"	257"
Overall Width	93"	93"
Discharge Conveyor	20" wide belting	20" wide belting
Discharge Height	32" above ground	32" above ground
Tub Conveyor Width	40"	40"
Door Opening	38" wide x 12" high	38" wide x 12" high
Tires	385 / 65 x 22.5 (x2 – single axle)	385 / 65 x 22.5 (x4 – tandem axle)
Weight	5600 lbs.	8050 lbs.

Unless otherwise indicated, all dimensions are in inches with standard equipment installed.
 Specifications subject to change without notice.
 Certain features shown may be optional.

Helm Welding (1983) Limited