



SUPER SF



AVAILABLE DECK SIZES

Engine	Deck Sizes
38.5HP* - Kawasaki® FX1000 EFI	60", 72"
40HP* - Vanguard® Big Block™ EFI Oil Guard	60", 72"



SUPER SF

Electric Actuator Deck Lift
Easily adjust your cutting height from 2.0" to 5.5".

60" and 72" VX™ Deck
7 ga. deckplate with 7 ga. stamped spindle mounts and a 11 ga. bull nose leading edge.

Kawasaki® FX EFI and Vanguard® EFI Oil Guard Engine
38.5 HP* and 40 HP* options.

Speed Control Bar Adjustment
Up to 15 mph with reduced speed up to 10 mph.



Semi Pneumatic Front Tires
13" front tires.

Hydro Oil Cooler
8" fan and 6-quart reservoir capacity.

Large Rear Tires
26" x 12" rear tires rear tires for traction and stability.

Dual Fuel Tanks
13.9 gal. fuel capacity.



SUPER SF

- ✔ **Strong Hydros**
Hydro-Gear® 21cc pumps and Parker® TG wheel motors
- ✔ **Service Friendly Design**
Designed to make maintenance and service fast and easy.
- ✔ **SmoothTrak™ Steering**
Precision control to help trim and maneuver easily around obstacles.
- ✔ **VX™ Deck**
Fabricated 7 ga. steel with 7 ga. wrappers engineered for extreme vacuum performance and cut quality.
- ✔ **26" Drive Tires**



ACCESSORIES

(Each sold separately)

- ▶ Mulch kit
- ▶ Mud Flap kit
- ▶ Light kit
- ▶ Stripe kit
- ▶ Fabric side bagger (3.5 bushels)
- ▶ Aluminum side bagger (3.3 bushels)
- ▶ Michelin® X® Tweel® Turf Tire



SUPER SF

ENGINE	
Manufacturer	Kawasaki® FX Series, Vanguard® Big Block™
HP	60", 72" deck: 38.5HP* - FX1000 EFI 60", 72" deck: 40HP* - Big Block™ EFI Oil Guard (Per SAE J1995)
Displacement	Kawasaki® 999cc • Vanguard® 993cc
Cooling	Air cooled
Air Cleaner	Remote Canister
Engine Warranty	3 year limited
DRIVE SYSTEM	
Type	Dual hydrostatic
Pumps	Hydro-Gear® 21cc
Wheel Motors	Parker® TG
Hydraulic Cooling	Oil cooler w/ 8" fan
Reservoir Capacity	6 quarts
Speed	Up to 15 mph (Using speed limiter: Up to 10 mph)
Parking Brakes	Hand operated drum brakes
DECKS	
Cutting Width	Side discharge: 60", 72"
Cutting Heights	2.0" - 5.5"
Deck Lift	Electric actuator
Depth	5.5"
Blades	3
Blade Length	60" deck: 20.50" • 72" deck: 24.50"
Blade Tip Speed	60" deck: 18,600 • 72" deck: 18,500
Spindles	Ductile cast iron with steel shafts and sealed ball bearings
Drive	Electric PTO clutch
Construction	7 ga. w/ 7 ga. wrappers
Spindle Mounts	Reinforced 7 ga. stamped disc
Impact/Trim Areas	11 ga. formed channel w/ rolled edge
Anti-scalp Wheels	n/a
CONSTRUCTION	
Frame	1.5" x 3" steel tubing
Engine Plate	7 ga.
Operator Platform	7 ga.
Front Axle	Fabricated w/ tapered roller bearings
Front Caster Wheels	Tapered wheel bearings and debris cap
Front Caster Forks	Fabricated 1/2" steel
Operator Pad	Bolstered / Adjustable
GENERAL	
Fuel Capacity	13.9 gallons
Front Tire	13 x 6.5 - 6 semi pneumatic
Drive Tire	26 x 12 - 12
DIMENSIONS	
Weight	60": 1450 lbs • 72": 1500 lbs
Height	50"
Length	60": 79.2" • 72": 81.7"
Width w/Chute Up	60": 61.6" • 72": 73.6"
Tire Width	53.5"
Trim Side	60": 4.1" • 72": 12.5"
PRODUCTIVITY**	
Acres Per Hour	60": 7.27 • 72": 8.73

Specifications are subject to change without notice.

* As rated by the engine manufacturer.

** Number based on 80% efficiency. This rating is to account for actual mowing conditions including overlapping, turning and terrain. Kawasaki is a registered trademark owned by KAWASAKI JUKOGYO KABUSHIKI KAISHA. Vanguard is a registered trademark owned by Briggs & Stratton Corporation. Parker is a registered trademark owned by Parker Intangibles LLC. Hydro-Gear is a registered trademark owned by Hydro-Gear Limited Partnership. Michelin, X and Tweel are registered trademarks owned by COMPAGNIE GÉNÉRALE DES ÉTABLISSEMENTS MICHELIN.