TURF \ BATWING

COMMERCIAL GRADE. FINISH CUT. NO COMPROMISES.

Introducing the all-new commercial Turf Batwing® finish mower line. Engineered with proven components for best-in-class cut quality* and extreme durability. Tackle challenging terrains and overcome demanding commercial applications like never before with the new Turf Batwing.

TBW12.40 | TBW15.40 | TBW17.40 TRIPLE-DECK FLEXWING FINISH MOWERS





THE TURF BATWING INCLUDES THE CUTTING TECHNOLOGY FROM THE #1 RATED TURFKEEPER PROSPRATED BEST IN CUT QUALITY IN INDEPENDENT TESTING.

For more information visit woodsequipment.com





With its unique deck design and heavy duty steel construction, the new commercial Turf Batwing finish mower line combines unsurpassed cut quality and extreme durability. This rugged workhorse is capable of withstanding 2,000 hours of continuous runtime and features premium caster wheels to tackle uneven terrain. What's more, its unique high-lift blades and baffling design produce unrivaled cut quality*, making it the best choice when you mean business on your job.

SPECIFICATIONS	TBW12.40	TBW15.40	TBW17.40
Tractor PTO (hp)	30-80	35-80	40-80
Hitch	CAT 1, Drawbar CAT 2, Drawbar		
Hitch Adjustment	Floating clevis, multi-position		
Cut Width (in)	144	180	204
Cut Height (in)	1.5 - 5.5		
Wing Deck Cut Width (in)	48	60	72
Center Deck Cut Width (in)	60	72	72
Deck Overlap (in)	6.0		
Overall Width (in)	145	183	205
Transport Width (in)	88	97	101
Max. Overall Length (in)	171	182	
Transport Length (in)	167	176	
Splitter Gearbox (hp)	80		
Blade Tip Speed (fpm)	18,000	18,100	
Drive Type	Gearbox over v-belt		
Input Driveline	CAT 4 CV (const. vel.)		
Wing Drivelines	CAT 3		
Transport Tires (in)	(2) 20.5 x 8-10		
Caster Wheel Bearings	Tapered roller bearings		
Caster Wheels (in)	(10) 15 x 6-6 pneumatic	(10) 18 x 9.5	-8 pneumatic
Wing Deck Lift Cylinders	3.0 x 10 single-acting		
Center Deck Lift Cylinders	3.0 x 8 single-acting		
Trailer Frame Construction (in)	4.0 x 4.0 x .25 sq tube		
Deck Thickness	7 gauge		
Blade Spindles	(9) ductile iron		
Blade Spindle Bearings	Triple ball bearings		
Blade Dimensions (in)	(6) .25 x 2.5 x17 (3) .25 x 2.5 x 21	(6) .25 x 2.5 x 21 (3) .25 x 2.5 x 25	(9) .25 x 2.5 x 25

FEATURES		
Transport Lock	Automatic, manual release	
Transport Tires	Highway speed-rated	
Cut Height Adjustment	Spacer on caster	
Caster Pivot Bushings	Yes	
Belt Construction	HB-section, Aramid	
Belt Adjustment	Spring-loaded idler w/bearing pivot	
Light Kit	Standard	
Hydraulic Wing Unlock	Optional	
Gearbox Warranty	6-year	
Mower Warranty	1-year	
Spindle Warranty	3-year	

TBW12.40 | TBW15.40 | TBW17.40

TRIPLE-DECK FLEXWING FINISH MOWERS





6-YEAR GEARBOX WARRANTY The industry's most

comprehensive warranty covers both the gearbox and seals



HANDLE RUGGED **TERRAIN**

Repositioned, extra-large caster wheels better handle rugged terrain.



WARRANTY

WIDER DISCHARGE AREA

Wider discharge area allows clippings to flow through effortlessly, without clogging.



IMPROVED BELT DRIVE DESIGN

Handles more horsepower than ever before to maintain superior cut quality at higher speeds



EASY SHIELD REMOVAL

No tools needed to access belt sheaves, belt and spring-loaded idler.



OPTIONAL FRONT AND REAR **ROLLERS**

Anti-scalp protection for uneven terrain.



OPTIONAL CHAIN SHIELDING

Helps prevent discharge of foreign objects.

WOODS_® | Woods Equipment Company

2606 South Illinois Route 2, Oregon, Illinois 61061 tel 800-319-6637 woodsequipment.com

WARNING! Some images may show safety shields removed to provide a better view. Equipment should never be operated with any safety shield removed. Some machines in this brochure may be shown with optional equipment. Always operate machines in accordance with supplied operator's manuals. ©2022 Woods Equipment Company. All rights reserved. WOODS, Woods logo, and Turf Batwing logo are trademarks of Woods Equipment Company. All other trademarks, trade names, or service marks not owned by Woods Equipment Company that appear in this brochure are the property of their respective companies or mark holders. Specifications subject to change without notice.

