



| Capacities                                  |                | Metric                   |
|---|----------------|--------------------------|
| Max. capacity                               |                | 3628.70 kg               |
| Max. lifting height                         |                | 12.96 m                  |
| Max. outreach                               |                | 8.69 m                   |
| Neight and dimensions                       |                |                          |
| Overall length to carriage                  | l11            | 6.30 m                   |
| Overall length (with forks)                 | l1             | 7.51 m                   |
| Overall width                               | b1             | 2.48 m                   |
| overall height                              | h17            | 2,44 m                   |
| Vheelbase                                   | у              | 3.50 m                   |
| Fround clearance                            | m4             | 0.46 m                   |
| Overall cab width                           | b4             | 0.95 m                   |
| ilt-up angle                                | a4             | 34 °                     |
| ilt-down angle                              | a5             | 96 °                     |
| xternal turning radius                      | Wa3            | 4 m                      |
| Inladen weight                              | was            | 10864 kg                 |
| ires type                                   |                | Pneumatic                |
| orks length / width / section               | l / e / s 1219 | 9 mm x 101 mm / 50.80 mm |
| rame leveling longitudinal +/-              | 17 67 3        | 10 °                     |
| Performances                                |                | 10                       |
| ifting                                      |                | 11 s                     |
| •   |                | 6 \$                     |
| owering                                     |                |                          |
| xtension<br>tetraction                      |                | 17 s                     |
|   |                | 11 s                     |
| Crowd                                       |                | 4 s                      |
| Dump  |                | 6 s                      |
| ingine                                      |                |                          |
| ingine brand                                |                | Deutz                    |
| ingine norm                                 |                | Tier 4 final             |
| ingine model                                |                | TCD 3.6 L4               |
| Number of cylinders / Capacity of cylinders |                | 4 - 3600 cm <sup>3</sup> |
| C. Engine power rating - Power (kW)         |                | 74 Hp / 55 kW            |
| Max. torque / Engine rotation               |                | 390 Nm @ 2300 rpm        |
| ransmission                                 |                |                          |
| Fransmission type                           |                | Powershift               |
| Number of gears (forward / reverse)         |                | 5 / 3                    |
| Max. travel speed                           |                | 32 km/h                  |
| Parking brake                               |                | SAHR                     |
| Service brake                               |                | Wet disc brakes          |
| Hydraulics                                  |                |                          |
| dydraulic pump type                         |                | Axial piston             |
| lydraulic flow / Pressure                   |                | 151 l/min-275.80 bar     |
| ank capacities                              |                |                          |
| ingine oil                                  |                | 8.51 l                   |
| lydraulic oil                               |                | 136.30 l                 |
| uel tank                                    |                | 144 l                    |
| loise and vibration                         |                |                          |
| Noise at driving position (LpA)             |                | 80 dB                    |
| Miscellaneous                               |                |                          |
| iteering wheels (front / rear)              |                | 2 / 2                    |
| Drive wheels (front / rear)                 |                | 2 / 2                    |





Siège Social P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095 Tel: (262) 334-9461 - Fax: (262) 338-7517 www.gehl.com



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend