V230 - NEW

SKID LOADERS



GEHL

Capacities		Metric
Operating Capacity At 50% Tipping Load		1043.26 kg
Operating Weight		3497 kg
Jnladen weight		3150 kg
Fipping capacity		2086.53 kg
Neight and dimensions		
Operating Weight - Approximate		3497 kg
Overall Operating Height - Fully Raised	h27	4039 mm
Height to Hinge Pin – Fully Raised	h28	3086 mm
Overall Height to top of ROPS	h17	2058 mm
Dump angle at full height	a5	42 °
Dump height	h29	2312 mm
Overall length with bucket	l16	3589 mm
Dump reach - Full height	r6	826 mm
Rollback Angle at Full Height	a4	92 °
Seat to ground height	h30	978 mm
Overall width less bucket	b1	1707 mm
Fround clearance	m4	203 mm
Overall length - Less Bucket	12	2789 mm
Clearance Radius - Front with Bucket	b18	2171 mm
Clearance Circle - Front without Bucket	b19	1308 mm
Clearance Circle - Rear	wa1	1689 mm
Performances	war	1007 11111
Fravel Speed with Two-Speed Option - Maximum		20 km/h
Fravel speed (unladen)		12.70 km/h
Engine		12.7 O KIII/11
ingine brand		Yanmar
ingine model		4TNV98CT-XNGL
ingine norm		Stage V, Tier 4
Gross Power (kW)		53.70 kW
let Power (kW)		52.70 kW
Max. torque / Engine rotation		294 Nm / 1800 rpm
Number of cylinders		294 Will 7 1800 Tp111
ingine cooling system		Water
Battery voltage		12 V
Alternator - Ampere		100 A
Starter (kW)		3 kW
Hydraulics		3 KVV
•		86.50 l/min
Standard flow - Auxiliary hydraulics		239.59 bar
Auxiliary Hydraulic Pressure		
High-Flow Auxiliary Hydraulics – Option		114 l/min
ligh-Flow Auxiliary Hydraulics Pressure – Option		229.25 bar
Fank capacities		405
Fuel tank		106 l 3.30 l
Displacement		





Siège Social P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095 Tel: (262) 334-9461 - Fax: (262) 338-7517 www.gehl.com



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS West Bend