# 2024 OUTLANDER X xc 1000R



#### PACKAGE HIGHLIGHTS

- Tri-Mode Dynamic Power Steering (DPS™)
- Visco-Lok<sup>†</sup> QE auto-locking front differential
- FOX† PODIUM† 1.5 RC2 shocks
- · A-arms HMWPE protectors
- 26 in. ITP† Terracross radial tires with 14 in. aluminum beadlock wheels
- · Front, center & footwell aluminum skid plates
- Aluminum sport bumper with aluminum pre-runner and top brace
- · Aluminum taper-profile handlebar with full wrap handguards
- 7.6 in. wide digital display

## Chalk Gray & Can-Am Red

| ENGINE               | 1000R   |
|----------------------|---|
| Туре                 | 91 hp, Rotax® 976 cc V-twin, liquid-cooled  |
| Fuel Delivery System | Intelligent Throttle Control (iTC™)<br>with Electronic Fuel Injection (EFI)         |
| Transmission         | CVT<br>L/H/N/R/P  |
| Drive Train          | Selectable 2WD / 4WD with Visco-Lok <sup>†</sup> QE auto-locking front differential |
| Driving Assistance   | ECO / Standard / Sport modes<br>Intelligent Engine Braking (iEB™)                   |
| Power Steering       | Tri-Mode Dynamic Power Steering (DPS™)  |
| SUSPENSIONS          |   |
| Front Suspension     | Arched double A-arm with front sway bar 9.2 in. (23.3 cm) travel                    |
| Front Shocks         | FOX† 1.5 PODIUM† RC2  |
| Rear Suspension      | Torsional Trailing arm Independent (TTI)<br>9.9 in. (25.1 cm) travel                |
| Rear Shocks          | FOX <sup>†</sup> 1.5 PODIUM <sup>†</sup> RC2  |
| TIRES & WHEELS       |   |
| Front / Rear Tires   | ITP† Terracross 26 x 8 / 10 x 14 in.  |
| Wheels               | 14 in. cast-aluminum beadlock   |
| BRAKES               |   |
| Front                | Dual 214 mm disc brakes with hydraulic twin-piston calipers                         |
| Rear                 | Single 214 mm disc brake with hydraulic twin-piston caliper                         |

### **DIMENSIONS & CAPACITIES**

| Estimated Dry Weight* | 895 lb (406 kg)                             |
|-----------------------|---|
| LxWxH                 | 86 x 48 x 49.5 in. (218.4 x 121.9 x 126 cm) |
| Wheelbase             | 51 in. (129.5 cm)                           |
| Ground Clearance      | 11 in. (27.9 cm)                            |
| Seat Height           | 34.5 in. (87.7 cm)                          |
| Rack Capacity         | Rear: 200 lb (90 kg)                        |
| Storage Capacity      | 5.7 gal (21.4 L)                            |
| Towing Capacity       | 1,650 lb (750 kg)                           |
| Fuel Capacity         | 5.4 gal (20.5 L)                            |
| FEATURES              |   |

#### FEATURE

| Gauge           | 7.6 in. wide digital display   |
|-----------------|--|
| Instrumentation | DC outlet, 15 A connector  |
| Ignition        | RF Digitally Encoded Security System (D.E.S.S.™)   |
| Lighting        | LED headlights   |
| Winch           | Prewired for available winch   |
| Seat            | Standard   |
| Handlebar       | Aluminum taper-profile handlebar with full wrap handguards   |
| Protection      | Aluminum front bumper with pre-runner and top brace<br>Front, center and footwell aluminum skid plates<br>A-arms HMWPE protectors<br>Mudguards |

## WARRANTY & EXTENDED SERVICE

| Factory Warranty          | 6-month BRP limited warranty            |
|---------------------------|---|
| Extended Service<br>Terms | B.E.S.T. term available up to 36 months |



