Can-am. MAVERICK SPORT X mr 1000R

HIGHLIGHTS

Rear

DARING	Sturdy engine and transmission Enhanced comfort and meaningful functionalities Can-Am design
PRECISE	Easy handling and capabilities Suspension designed for performance Ultra-resistant chassis
CONFIDENT	Perfectly tuned Enhanced protection More adventure and less maintenance
PLATFORM FEATURES	• 90.6 in. wheelbase • 15 in. of ground clearance • 14.75 in. suspension travel • Dynamic Power Steering (DPS™) • SPORT/ECO™ modes • Premium half door • Mudguard
SPECIFIC TO X mr PACKAGE	• 64 in. wide with arched A-arm • Smart-Lok* front differential • Snorkeled engine air intake and CVT • FOX* 2.5 PODIUM* QS3 piggyback shocks • 30 in. ITP* Cryptid* tires • 14 in. cast-aluminum wheels • 4,500 lb (2,041 kg) winch with synthetic cable • Fender flare extensions • X-package graphics/seats • 7.6 in. digital display with keypad • Can-Am LED signature and premium tail light
ENGINE	1000R
Туре	100 hp, Rotax® 976 cc, V-twin, liquid-cooled

ENGINE	1000R
Туре	100 hp, Rotax® 976 cc, V-twin, liquid-cooled with strategically positioned engine air intake
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	Quick Response System (QRS) CVT with high-airflow ventilation Strategically positioned CVT air intakes and exhaust Lower gearing ratio and Electronic Drive Belt Protection Extra-L/H/N/R/P
Drive Train	Lockable front differential with exclusive Smart-Lok technology True 4-mode traction system: 2WD/4WD with front diff. lock/4WD MUD/4WD TRAIL
Driving Assistance	Electronic Hill Descent Control SPORT/ECO™ modes
Power Steering	Dynamic Power Steering (DPS)
SUSPENSIONS	
Front Suspension	Arched double A-arm with sway bar/14.8 in. (37.6 cm) travel
Front Shocks	FOX 2.5 PODIUM piggyback with QS3 compression adjustment
Rear Suspension	Arched TTA with sway bar/14.8 in. (37.6 cm) travel
Rear Shocks	FOX 2.5 PODIUM piggyback with QS3 compression adjustment
TIRES & WHEELS	
Front Tires	ITP Cryptid 30 x 9 x 14 in.
Rear Tires	ITP Cryptid 30 x 11 x 14 in.
Wheels	14 in. cast-aluminum
BRAKES	
Front	Dual 220 mm ventilated disc brakes



DIMENSIONS & CAPACITIES

0.11.10.11.20		
Estimated Dry Weight	1,617 lb (733.5 kg)	
Chassis/Cage	Profiled cage, ROPS approved	
LxWxH	122 x 64 x 74.25 in. (309.8 x 162.6 x 188.6 cm)	
Wheelbase	90.6 in. (230.1 cm)	
Ground Clearance	15 in. (38.1 cm)	
Cargo Box Capacity	300 lb (136 kg)	
Towing Capacity	1,500 lb (680 kg)	
Storage Capacity	Total: 5.3 gal (20.2 L) Glove box: 4.1 gal (15.6 L) Driver storage: 0.4 gal (1.5 L) Center console and cup holders: 0.8 gal (3.1 L)	
Fuel Capacity	10 gal (38 L)	

FEATURES

7.6 in. wide digital display with keypad: speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT/ECO™ modes, seat belt and 4 x 4 indicator, front and rear diff. lock indicators, diagnostics, clock, battery voltage, engine temperature
Lighter type DC outlet in console (20 A)
650 W
Two 55 W reflectors with unique Can-Am LED signature and LED tail lights with halo glow effect
4,500 lb (2,041 kg) winch with synthetic rope
Adjustable tilt steering
Integrated front steel bumper Premium half doors Full skid plate Mudguards Fender flare extensions Front tow hook
2 in. hitch receiver

WARRANTY & EXTENDED SERVICE

Factory Warranty	6-month BRP limited warranty
Extended Service Terms	B.E.S.T. term available up to 30 months



with hydraulic twin-piston calipers

Dual 220 mm ventilated disc brakes with hydraulic twin-piston calipers