### 2022

# Can-am. MAVERICK X3 MAX X mr TURBO RR

#### **HIGHLIGHTS**

	<ul> <li>14 in. of ground clearance</li> <li>High-torque Dynamic Power Steering (DPS™)</li> </ul>
	• 22 in. suspension travel
	FOX 2.5 PODIUM QS3 piggyback shocks     Rear tow hook
SPECIFIC TO	Belt-monitoring system
X mr TURBO RR PACKAGE	• 200 hp Turbo RR engine
	<ul> <li>Smart-Lok™* front differential</li> </ul>
	Snorkeled engine air intake and CVT
	• 14 in. aluminum beadlock wheels
	30 in. ITP Cryptid tires     Front bumper, half-doors
	• Front bumper, nan-doors • Front tow hook
	HMWPE full skid plate
	• 4,500 lb (2,041kg) winch with synthetic rope
	• X-package graphics/seats
	• 7.6 in. digital display with keypad
	Can-Am LED signature
	• 850 W magneto
	Painted color

ENGINE	TURBO RR
Туре	200 hp, Rotax ACE (Advanced Combustion Efficiency) 900 cc turbocharged triple-cylinder engine, liquid-cooled with integrated intercooler, high-perfomance air filter and strategically positioned engine air intake
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	PDrive primary and Quick Response System X (QRS-X) CVT, high airflow with strategically positioned CVT air intake and exhaust, L/H/N/R/P
Drive Train	Lockable front differential with exclusive Smart-Lok technology. True 4-mode traction system: 2WD/4WD with front diff. lock/4WD MUD/4WD TRAIL
Power Steering	High-torque Tri-Mode Dynamic Power Steering (DPS)
SUSPENSIONS	
Front Suspension	Arched double A-arm with sway bar/22 in. (55.9 cm) travel/Trophy truck-inspired arms
Front Shocks	FOX 2.5 PODIUM piggyback with QS3 compression adjustment
Rear Suspension	4-link Torsional Trailing-arm X (TTX) with sway bar and arched lower links/22 in. (55.9 cm) travel
Rear Shocks	FOX 2.5 PODIUM piggyback with QS3 compression adjustment and bottom-out control
TIRES & WHEELS	
Front Tires	ITP Cryptid 30 x 9 x 14 in.
Rear Tires	ITP Cryptid 30 x 11 x 14 in.
Wheels	14 in. cast-aluminum beadlock
BRAKES	
Front	Dual 262 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 248 mm ventilated disc brakes with hydraulic twin-piston calipers



Liquid Titanium & Magma Red / TURBO RR

## DIMENSIONS & CAPACITIES

Estimated Dry Weight

Chassis/Cage	Dual-phase 980 steel
LxWxH	165 x 74.2 x 68 in. (419.1 x 188.5 x 172.7 cm)
Wheelbase	135 in. (342.9 cm)
Ground Clearance	16 in. (40.6 cm)
Rack Capacity	150 lb (68 kg) with LinQ™ quick-attach
Storage Capacity	Total: 3 gal (11.4 L) Glove box: 1.6 gal (6.2 L) Central console: 1.1 gal (4.1 L) Cup holders: 0.3 gal (1.1 L)
Fuel Capacity	10.5 gal (40 L)
FEATURES	
Gauge	7.6 in. wide digital display with keypad: speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT/ECO™ mode, seat belt and 4 x 4 indicator, front and rear diff. lock indicators, diagnostics, clock, battery voltage, engine temperature, DPS mode
Instrumentation	Lighter-type DC outlet in central console
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button
Lighting	LED headlights and tail lights with unique Can-Am LED signature
Winch	4,500 lb (2,041 kg) winch with synthetic rope
Magneto	850 W
Protection	Front bumper Half doors Front and rear tow hooks

1,991 lb (903.1 kg)

## WARRANTY & EXTENDED SERVICE

Factory Warranty	6-month BRP limited warranty
Extended Service Terms	B.E.S.T. term available up to 30 months



HMWPE full skid plate

