2022

Can-am. MAVERICK X3 X mr TURBO RR 72"

HIGHLIGHTS

Rear

DEFIANT	 Trademark Can-Am DNA with next-generation design Low seating position Ergo-Lok cockpit with four-way adjustable seats
POWERFUL	 Industry-leading 200 hp turbocharged and intercooled Rotax® ACE engine Advanced airflow dynamics QRS-X transmission
PRECISE	TTX suspension with industry-leading travel Ultra efficient and lightweight chassis Sharpest handling features
PLATFORM FEATURES	 • 72 in. wide • 102 in. wheelbase • 16 in. of ground clearance • High-torque Dynamic Power Steering (DPS™) • 22 in. suspension travel • FOX 2.5 PODIUM QS3 piggyback shocks • Rear tow hook
SPECIFIC TO X mr TURBO RR 72" PACKAGE	Belt-monitoring system 200 hp Turbo RR engine Smart-Lok™ front differential Snorkeled engine air intake and CVT 14 in. aluminum beadlock wheels 30 in. ITP Cryptid tires Front bumper, half-doors Front tow hook HMWPE full skid plate 4,500 lb (2,041kg) winch with synthetic rope X-package graphics/seats 7.6 in. digital display with keypad Can-Am LED signature 850 W magneto Painted color

ENGINE	TURBO RR
Туре	200 hp, Rotax ACE (Advanced Combustion Efficiency) 900 cc turbocharged triple-cylinder engine, liquid-cooled with integrated intercooler, high-perfomance air filter and strategically positioned engine air intake
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	PDrive primary and Quick Response System X (QRS-X) CVT, high airflow with strategically positioned CVT air intake and exhaust, L/H/N/R/P
Drive Train	Lockable front differential with exclusive Smart-Lok technology. True 4-mode traction system: 2WD/4WD with front diff. lock/4WD MUD/4WD TRAIL
Power Steering	High-torque Tri-Mode Dynamic Power Steering (DPS)
SUSPENSIONS	
Front Suspension	Arched double A-arm with sway bar/22 in. (55.9 cm) travel/Trophy truck-inspired arms
Front Shocks	FOX 2.5 PODIUM piggyback with QS3 compression adjustmen
Rear Suspension	4-link Torsional Trailing-arm X (TTX) with sway bar and arched lower links/22 in. (55.9 cm) travel
Rear Shocks	FOX 2.5 PODIUM piggyback with QS3 compression adjustment and bottom-out control
TIRES & WHEELS	
Front Tires	ITP Cryptid 30 x 9 x 14 in.
Rear Tires	ITP Cryptid 30 x 11 x 14 in.
Wheels	14 in. cast-aluminum beadlock
BRAKES	
Front	Dual 262 mm ventilated disc brakes with hydraulic twin-piston calipers

Dual 248 mm ventilated disc brakes with hydraulic twin-piston calipers



1,758 lb (797.4 kg)

Dual-phase 980 steel

6-month BRP limited warranty

B.E.S.T. term available up to 30 months

Liquid Titanium & Magma Red / TURBO RR

DIMENSIONS & CAPACITIES

WARRANTY & EXTENDED SERVICE
Factory Warranty

Extended Service Terms

Estimated Dry Weight Chassis/Cage

LxWxH	132.3 x 74.2 x 68 in. (336 x 188.5 x 172.7 cm)
Wheelbase	102 in. (259.1 cm)
Ground Clearance	16 in. (40.6 cm)
Rack Capacity	200 lb (91 kg) with LinQ™ quick-attach
Storage Capacity	Total: 2.5 gal (9.4 L) Glove box: 1.6 gal (6.2 L) Central console: 0.8 gal (2.8 L) Cup holders: 0.1 gal (0.4 L)
Fuel Capacity	10.5 gal (40 L)
FEATURES	
Gauge	7.6 in. wide digital display with keypad: speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT/ECO™ mode, seat belt and 4 x 4 indicator, front and rear diff. lock indicators, diagnostics, clock, battery voltage, engine temperature, DPS mode
Instrumentation	Lighter-type DC outlet in central console
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button
Lighting	LED headlights and tail lights with unique Can-Am LED signature
Winch	4,500 lb (2,041 kg) winch with synthetic rope
Magneto	850 W
Protection	Front bumper Half doors Front and rear tow hooks HMWPE full skid plate Rear tow hook



