

## **HIGHLIGHTS**

- Rotax® V-Twin engine options
- · Arched double A-arm front suspension with front sway bar
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS)
- 3,500 lb (1,588 kg) winch
- · Heavy-duty front and rear bumpers
- · Handlebar wind deflectors
- Painted plastics for premium look
- 14 in. cast-aluminum wheels
- 26 in. ITP Terracross radial tires
- Surrounding Spar Technology (SST) G2 frame with Geometric Contact Control
- Torsional Trailing arm Independent (TTI) rear suspension
- 650 W magneto
- High-strength, multifunction racks with LinQ™ quick-attach accessory system
- 5.7 gal (21.4 L) water-resistant rear compartment



ENGINES	650	850	1000R
Туре	62 hp, Rotax 650 cc V-twin, liquid-cooled	78 hp, Rotax 854 cc V-twin, liquid-cooled	91 hp, Rotax 976 cc V-twin, liquid-cooled
Fred Delivery Overters	Electronic Fuel	· ·	
Fuel Delivery System	Injection (EFI)	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)	
Transmission	CVT, P/R/N/H/L, standard engine braking		
Drive Train	Selectable 2WD/4WD with Visco-Lok† QE auto-locking front differential		
Power Steering	Tri-Mode Dynamic Power Steering (DPS)		
SUSPENSIONS			
Front Suspension	Arched double A-arm with front sway bar		
Front Shocks	9.2 in. (23.3 cm) travel Oil		
Rear Suspension	Torsional Trailing arm Independent (TTI) 9.9 in. (25.1 cm) travel		
Rear Shocks	Oil		
TIRES & WHEELS			
Front Tires	ITP Terracross 26 x 8 x 14 in.		
Rear Tires	ITP Terracross 26 x 10 x 14 in.		
Wheels	14 in. cast-aluminum		
BRAKES			
Front	Dual 214 mm disc brakes with hydraulic twin-piston calipers		
Rear	Single 214 mm disc brake with hydraulic twin-piston caliper		

DIMENSIONS & CAPACITIES	650	850	1000R
Estimated Dry Weight*	749 lb (341kg)	800 lb (363 kg)	826 lb (375 kg)
LxWxH	86 x 48 x 49.5 in. (218.4 x 121.9 x 126 cm)		
Wheelbase	51 in. (129.5 cm)		
Ground Clearance	11 in. (27.9 cm)		
Seat Height	34.5 in. (87.7 cm)		
Rack Capacity	Front: 100 lb (45 kg)/Rear: 200 lb (90 kg)		
Storage Capacity	Rear: 5.7 gal (21.4 L)		
Towing Capacity	1,650 lb (750 kg)		
Fuel Capacity	5.4 gal (20.5 L)		
Gauge	4.5 in. digital display: speedometer, tachometer, odometer, trip and hour meters, gear position, 4 x 4 indicator, temperature, engine lights, electronic fuel gauge and clock		
Instrumentation	Lighter-type DC outlet in console, standard connector in the back (15 A)		
Anti-Theft System	N/A		y Encoded em (D.E.S.S.™)
Lighting	230 W from twin 60 W projectors and dual 55 W reflectors with tail light/brake light		
Winch	3,500 lb (1,588 kg) winch		
Seat	Standard		
Protection	Heavy-duty front and rear bumpers Handlebar wind deflectors		

## WARRANTY & EXTENDED SERVICE

Factory Warranty	6-month BRP limited warranty	
Extended Service Terms	B.E.S.T. term available up to 36 months	

Mudguards

