


2026 DEFENDER MAX XT



PACKAGE OPTIONS

- 10.25 in. touchscreen display (including premium steering wheel with controls and rear camera)

PACKAGE HIGHLIGHTS

- Quick-4Lok™ auto-locking front differential
- Dynamic Power Steering (DPS™)
- Speed limiter
- Brake Holding Mechanism
- 65 in. wide with arched double A-arm and sway bar
- 29 in. XPS Trail King 2
- 4,500 lb (2,041 kg) winch with synthetic cable
- Full heavy-duty HMW plastic skid plate
- Full hard roof
- Heavy-duty front bumper
- Mudguards
- LED headlights and LED taillights with back up light

ENGINE	HD11
Type	95 hp / 70 lb-ft Rotax® ACE (Advanced Combustion Efficiency) 999 cc triple cylinder, liquid-cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	pDrive primary and Quick Response System X (QRS-X) CVT with high airflow and Electronic Drive Belt Protection L / H / N / R / P
Drive Train	Selectable Turf Mode / 2WD / 4WD with Quick-4Lok auto-locking front differential
Driving Assistance	CVT engine braking Sport / Normal / Work modes Speed limiter
Power Steering	High torque Tri-Mode Dynamic Power Steering (DPS)

SUSPENSIONS

Front Suspension	Arched double A-arm with sway bar / 12 in. (30.5 cm) suspension travel
Front Shocks	Twin-tube gas charged shocks
Rear Suspension	Arched double A-arm / 12 in. (30.5 cm) suspension travel
Rear Shocks	Twin-tube gas charged shocks

TIRES & WHEELS

Front / Rear Tires	XPS Trail King 2 29 x 9/11 x 14 in.
Wheels	14 in. cast-aluminum

BRAKES

Front	Dual 262 mm disc brakes with hydraulic twin-piston calipers (32 mm)
Rear	Dual 236 mm disc brakes with hydraulic twin piston caliper (28 mm)
Brake Holding Mechanism	Brake Holding Mechanism

DIMENSIONS & CAPACITIES

Cage	Profiled cage ROPS approved
Estimated Dry Weight	2,170 lb (984 kg)
L x W x H	162.4 x 65 x 81.4 in. (412 x 165 x 207 cm)
Wheelbase	117.5 in. (298 cm)
Ground Clearance	14 in. (35.6 cm)
Cargo Box Dimensions	38 x 54.5 x 12 in. (96.5 x 138.4 x 30.5 cm)
Cargo Box Capacity	1,000 lb (454 kg) / California only: 600 lb (272.2 kg)
Power Tilt Bed	N/A
Tailgate Load Capacity	250 lb (113.4 kg)
Storage Capacity	• Weather resistant above gage glove box including protected cellphone area, USB-A plug if vehicle is equipped with 10.25 infotainment system • Weather resistant passenger glove box with USB-C, USB-A & DC outlet • Cubby storage and lower dash storage • 3.7 gal (14 L) removable bin
Towing Capacity	2,500 lb (1,134 kg)
Payload Capacity	1,475 lb (669 kg)
Fuel Capacity	11.9 gal (45 L)
Person Capacity	6

FEATURES

Gauge	4.5 in. wide digital display with keypad OR 4.5 in. wide digital display with keypad & 10.25 in. touchscreen display
Battery	400 CCA (32 amp/h) 12 V (cargo outlet)
Magneto	650 W
Instrumentation	• USB outlets • Lighter DC outlet • Cargo 12 V outlet
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start / Stop button
Lighting	LED headlights • LED taillights with back up light
Winch	4,500 lb (2,041 kg) winch with synthetic cable
Seat	Adjustable driver's seat • 40/20/40 bolster
Steering Wheel	Premium steering wheel Adjustable steering wheel with full tilt-up feature
Protection	• Full heavy-duty HMW plastic skid plate • Full hard roof • Heavy-duty front bumper • Mudguards • Door safety net
Hitch Type	2 in. hitch receiver

WARRANTY & EXTENDED SERVICE

Factory Warranty	1-year BRP limited warranty
Extended Service Terms	B.E.S.T. term available up to 30 months



© 2025 Bombardier Recreational Products Inc. (BRP). All rights reserved. ®, TM and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. † Visco-Lok is a trademark of GKN Viscodrives GmbH. All other trademarks are the property of their respective owners. For other jurisdictions, see your local dealer. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring obligation. Some models depicted may include optional equipment. Read the side-by-side vehicle (SxS) operator's guide and watch the safety DVD before driving. For your safety, wear a helmet, eye protection and other protective gear. Fasten lateral net and seat belt at all times. Always remember that riding, alcohol and drugs don't mix. SxSs are for off-road use only. Never ride on paved surfaces or public roads. Operator must be at least 16 years old. Passenger must be at least 12 years old and able to hold hand grips and plant feet while seated against the backrest. Never engage in stunt driving and avoid excessive speed. Ride responsibly.

