

## makes a difference

# Fleet Aluminum Brightener

Fleet Aluminum Brightener is an extra-strength, acid-based, aluminum cleaner and brightener designed for non-polished aluminum tanks and trailers, aluminum wheels and for preparing aluminum for painting. Fleet Aluminum Brightener is effective in removing grease, oils, baked-on carbon and diesel smoke. This formula is low foaming..

#### **Benefits**

- Cleans and Brightens Aluminum
- Economical Dilution Rates
- Safer than Hydrofluoric Acid products

**Dilution Ratio:** 1:5 to 1:20, 5 gallons makes 105 gallons

**To Apply:** DO NOT use on glass, polished aluminum or anodized aluminum. DO NOT use Fleet Aluminum Brightener through the

high pressure pump. Use through a downstream injector only to prevent damage to the pump.









**Directions:** INDUSTRIAL USE ONLY. Read the Safety Data Sheet thoroughly before using this product. For heavy soils, mix with water at a 1:5 dilution rate. For light soils, mix at 1:20 (pH 2.3 at dilution). Rapidly wet surface with diluted Fleet Aluminum Brightener and allow it to stand for a few minutes. Clean entire surface lightly with a pressure washer or brush, then rinse thoroughly with plenty of clean water.

#### **Product Information**

| Part No.    | Size   | Gross<br>weight | Dimensions<br>(L x W x H) inches | Ship<br>UPS |
|-------------|--------|-----------------|----------------------------------|-------------|
| 9.803-746.0 | 5 gal  | 52 lbs          | 12.5 x 12.5 x 15                 | No          |
| 9.803-747.0 | 55 gal | 560 lbs         | 23.5 x 23.5 x 35                 | No          |

| Safety                           |   |
|----------------------------------|---|
| HMIS Safety Rating: Health       | 2 |
| HMIS Safety Rating: Flammability | 1 |
| HMIS Safety Rating: Reactivity   | 0 |
| Personal Protective Equipment    | D |

OSHA/WHMIS/GHS-Compliant SDS available, listed with Infotrac. For emergency spills call 1-800-535-5053, International 1-352-323-3500.

#### **Technical Data**

Color: Light straw, clear

Scent: Sharp

Foam 1-5: 3 = Medium to 2= Low

**Reaction in Hard Water 1-5:** 2 = Fair

 ${\bf pH}$  at Full Strength: Less than 1

pH at Use Dilution (1:20 Ratio): 2.3

### Certifications

Kosher Certified: Use year round, not including Passover.

**Smog & Ozone:** in accordance with AQMD Rule 102, this product contains 0% photochemically reactive ingredients to contribute to smog or attack the earth's ozone layer.

**VOC:** This product contains 0.2% California Consumer Products VOC at 1:5 ratio.