

DEMCO
HEADER TRANSPORTS

**IT'S FAST
AND IT STEERS**



DON'T COMPROMISE



**Highway Speed
+
Tight Cornering**

DEMCO

Doing Our Best to Provide You the Best
www.demco-products.com | 800-543-3626

There are many imitators to the tricycle design of header transports but the clear leader is Demco. Demco's unique design offers the quality and durability to withstand the heaviest of loads. Whether you are looking for a storage transport or a transport to travel across the country, Demco has your needs covered.

KEY FEATURES ON ALL HEAD TRANSPORTS

Torsion Suspension Axles Standard

Makes for a smooth ride when towing. Absorbs shock on rough roads to make the Head Transport last longer.

Painted with Rubberized Undercoating

Keeps your Head Transport looking better longer by resisting rock chips better than traditional paint.

Standard Telescoping Tongue on all Head Transports

Makes the Head Transport easier to hook up

Features Demco's EZ Latch Coupler

2 5/16" ball coupler, safety chains and our EZ latch Coupler so you know it is hooked up right!

FEATURING DEMCO'S EXCLUSIVE EZ LATCH COUPLER

*Standard on Heavy Duty Head Transports



CHOOSING THE RIGHT HEADER TRAILER

	AWSpeed	Standard	HD
All Wheel Steer High Speed Header Transport Trailers		Heavy Duty Header Transport Trailers	Standard Header Transport Trailers
Capacity	21,000 lbs	11,200-20,000 lbs	20,000 lbs
Length	32'52'	20'-52'	32'-52'
4 Wheel Steering	✓	-	-
Highway Option	✓	-	-
Torsion Suspension Axles	✓	✓	✓
Rubberized undercoating	✓	✓	✓
Telescoping Tongue	✓	✓	✓
EZ-Latch Coupler	✓	✓	✓
Brakes	-	✓	✓



NEW! HIGH SPEED ALL WHEEL STEER HEAD TRANSPORT

32' • 38' • 42' • 48' • 52'

- DEMCO's newest Header Transport gives you the All Wheel Steer maneuverability along with the HIGH SPEED features of the Standard & Heavy Duty transports.
- All Header Transport features designed into 1 Header Transport
- As the Combine Headers get larger Demco's HIGH SPEED All Wheel Steer design will check all the boxes that you are looking for in a Header Transport.
- Available in 32' – 38' – 42' – 48' – 52' lengths

STANDARD HEAD TRANSPORT

20' • 24' • 28' • 32' • 38' • 44' • 48' • 52'

- 13 models ranging from 20' to 48' with rear single or tandem axle available on six sizes
- 6,000 lb axles
- 15" tires
- Optional front and rear fenders



HEAVY DUTY HEAD TRANSPORT

32' • 38' • 42' • 48' • 52'


- Equipped with 235/80R 16" tires
- 7,000 lb axles
- Uses 8 x 4 3/16" tubing - Larger HD's use 8 x 4 1/4" tubing
- Standard front and rear fenders



The Tricycle front design allows for short turns and superior high speed towing capability


With thousands of dollars invested in your corn head and more in your platform, trusting your investment to the best head transport on the market, would only be right!

**HIGH SPEED ALL WHEEL STEER
HEADER TRANSPORT**
32' • 38' • 42' • 44' • 48' • 52'



DIMENSIONS

	32	38	42	44	48	52
A	43'4"	48'10"	53'	52'	59'	63'
B	32'4"	37'10"	42"	44'	48'	52'
C	24'5"	30'3"	34'3"	32'4"	37'6"	35'10"
D	4'	4'	4'	5'6"	5'8"	5'10"
E	8'5"	8'5"	8'5"	8'5"	8'5"	8'5"




SPECIFICATIONS

	32	38	42	44	48	52
G.V.W.	20,000 lbs					
Wheel Size	16"	16"	16"	16"	16"	16"
Empty Weight (lbs)	4,070	4,470	5,020	5,650	5,970	6,000

STANDARD HEAD TRANSPORT

20' • 24' • 28' • 32' • 38' • 42' • 48' • 52'



DIMENSIONS


	20	24	28	32	38	44	48	52
A	31'	35'	39'	43'	48'6"	52'8"	58'6"	62'6"
B	20'4"	24'4"	28'4"	32'4"	37'10"	44'	48'	52'
C	19'8"	20'10"	24'10"	24'1"	30'6"	34'6"	37'8"	36'
D	8'4"	8'4"	8'4"	8'4"	8'4"	8'4"	8'4"	8'4"

SPECIFICATIONS

	20	24	28	32	38	44	48	52
G.V.W.	11,200 lbs	11,200 lbs	11,200 lbs	16,800 lbs	16,800 lbs	16,800 lbs	20,000 lbs	20,000 lbs
Wheel Size	15"	15"	15"	15"	15"	15"	16"	16"
Tire Size	225/75 R15	235/80 R16	235/80 R16					


HEAVY DUTY HEAD TRANSPORT

32' • 38' • 44' • 48' • 52'



DIMENSIONS

	32	38	44	48	52
A	42'10"	48'4"	52'6"	58'6"	62'6"
B	32'4"	37'10"	44'	48'	52'
C	24'7"	30'4"	34'4"	37'8"	36'
D	4'	4'	4'	5'6"	5'10"
E	8'5"	8'5"	8'5"	8'5"	8'5"



SPECIFICATIONS

	32	38	44	48	52
G.V.W.	20,000 lbs				
Wheel Size	16"	16"	16"	16"	16"
Tire Size	235/80 R16				