





5200 ENFORCER

A high-speed tillage machine, the 5200 ENFORCER, is engineered to level and uniformly mix soil and residue between three and five inches. The patent-pending blade mounts offer unmatched obstacle protection, clearance, and increased machine stability.

Four rows of concave blades replicate two passes with a tandem disk, resulting in a superior residue blend and field finish in one pass. The heavy-duty blade mounts and added clearance on the 5200 penetrate dry, hard ground and prevents plugging in wet soil.

The 5200's rubber suspension blade mounts allow each blade to flex up to five inches for industry-leading obstacle protection. Unlike a tandem disk, each blade faces obstacles on its own, which allows the 5200 to excel in rough, rocky fields. The blades tip under to create a suction that holds the 5200 in the ground when going through hard soil.

You can depend on the 5200 ENFORCER to perform fast, aggressively, and unmatched to easily dominate the most demanding field conditions.







5200 ENFORCER FEATURES

OPERATING DEPTH 3-5 in. **OPERATING SPEED (mph)** 5.5 - 9 **RESIDUE % AFTER ONE PASS** 50 - 80 **SEED BED PREP** GOOD **PRIMARY TILLAGE EXCELLENT** FIELD LEVELING **EXCELLENT WEED CONTROL EXCELLENT** CHEMICAL/FERTILIZER INCORPORATION **EXCELLENT RESIDUE MANAGEMENT EXCELLENT** SURFACE COMPACTION REMOVAL **EXCELLENT**

TOP DOWN FRONT VIEW

EXCELLENT

LAND RECLAMATION







SS	SIZE	WORKING WIDTH	CONCAVE BLADES #	TRANSPORT HEIGHT	TRANSPORT WIDTH	WEIGHT WITH HARROWS (LBS. APPROX.)	HP REQUIRED 15-20 PER FT.
. SPECS	12 ft.	12 ft. 1 in.	28	No Wings	13 ft. 10 in.	11,100	180 - 240
MODEL	16 ft.	15 ft. 5 in.	36	9 ft.	11 ft. 6 in.	15,600	240 - 320
Σ	19 ft.	18 ft. 9 in.	44	10 ft. 3 in.	15 ft. 2 in.	20,700	280 - 380
	22 ft.	22 ft. 1 in.	52	12 ft. 4 in.	15 ft. 2 in.	22,800	330 - 440
	25 ft.	25 ft. 5 in.	60	13 ft. 5 in.	15 ft. 2 in.	24,000	380 - 500
	29 ft.	28 ft. 9 in	68	14 ft. 7 in.	15 ft. 2 in.	27,900	430 - 580
	36 ft.	35 ft. 5 in.	84	14 ft. 6 in.	20 ft. 6 in.	37,200	540+
	39 ft.	38 ft. 9 in.	92	15 ft. 11 in.	20 ft. 6 in.	38,000	540+

Operation	Crop Type	Depth*
Fall residue management	All crops	3 in 5 in. (disk hubs must stay clear of field surface)
Seedbed preparation	All crops	2 in 3.5 in. depth varies by amount of residue cover
Nutrient Incorporation	All types	3 in 5 in.

^{*} Optional 24 in. blades are required for operating 5" deep











See our full line of products and find your local dealer at salfordgroup.com or call 1-866-442-1293

⊙ **y** □ in f ⊕ @salfordgroup

Products and specifications subject to change without notice and without liability therefore. Images may include optional equipment. Salford® is a registered trademark of Salford Group Inc. Copyright©2023 Salford Group Inc. 2023.03 # 10108969 - LITERATURE, SALFORD, 5200 ENFORCER



