MEYER FORMULA MIXER TRUCK MOUNT SPECIFICATIONS - TRANSMISSION PTO DRIVE

| MIXER MODEL | MINIMUM WHEEL BASE | MINIMUM CAB TO AXLE (CLEAR FRAME) *** | MINIMUM AFTER FRAME | AXLE TYPE | MINIMUM GVWR | MINIMUM FRAME SECTION MODULUS* | MINIMUM AXLE FRONT/ REAR | MINIMUM ENGINE HP | MINIMUM ENG DISPLACEMENT | MINIMUM TORQUE @ PTO ADAPTOR** |
|----------------|-----------------------|---|---------------------------|-----------|-----------------|-----------------------------------|-----------------------------|----------------------|-----------------------------|-----------------------------------|
| F585 SIDE DOOR | 195" | 132" | 66" | SINGLE | 45,000# | 17 | 12,000# / 33,000# | 300 HP | 8 LITER | 400 FT-LBS @ 100% PTO |
| F700 SIDE DOOR | 195" | 132" | 66" | TANDEM | 54,000# | 17 | 14,000# / 40,000# | 300 HP | 9 LITER | 400 FT-LBS @ 100% PTO |

12/29/2021 Revision: C

- * MIN FRAME SECTION MODULUS refers to strength of frame based on 110,000 PSI yield strength
- ** PTO ADAPTOR must have bolt pattern and pilot to accept a 1410 series driveline, SPICER# 3-2-159
- *** No braces, exhaust pipes, brackets, hardware, etc. behind cab and above frame rails, unless cab to axle dimension is taken from behind these features


Truck Recommendations:

- ~ Ground speed of 2 3mph at 1800 engine RPM is desired for feeding Install Auxillary Transmission (Drop Box) as far rearward as possible
- ~ Radiator Options: Feedlot, Reverse Fan, Prescreen, etc.
- ~ Throttle lock / cruise control at engine speed incremental up to 1800 RPM
- ~ Wide mirrors
- ~ Frame Splicing tapered and staggered (Talk to your truck shop)


Chelsea Smart Start Modulating PTO or equivalent is required

Mid-Frame Twin Screw Direct Drive Two Speed





SUPPLY A 7-PIN MALE & FEMALE PLUG OFF THE REAR OF THE CAB FOR LIGHT HOOK UP TO IMPLEMENT, LOCATED CENTRALLY BEHIND THE CAB. ORDER FROM MEYER #56-0005-2 & 56-0014-1.



TAILLIGHT CONVERTER

DEPENDING ON MAKE AND MODEL OF TRUCK IT MAY BE NECESSARY TO INSTALL A LIGHT CONVERTER, MEYER #56-0028. CONVERTER ALLOWS SIGNAL LIGHTS AND BRAKE LIGHTS TO OPERATE ACCORDING TO DOT LIGHTING REGULATIONS.

Note: If truck is supplied by the customer, it is the responsibility of the customer to work with a knowledgeable truck dealer to ensure all local and state transportation laws will be met where the truck is to be operated. If truck is supplied by a truck dealer, it is their responsibility to make the truck legal for road use by all state and local laws affecting the customer. Always follow federal, state and local laws for lighting, mud flaps, height, width, weight and operation. Over-width permits may be necessary in certain areas of