

# AS1240 XP



## The Apache Model AS1240 XP Sprayer

Comfort. Speed. Accuracy. Efficiency. That's exactly what you get from every Apache Sprayer. They're built to handle the toughest field conditions with a higher standard of comfort and performance. Because all we do is build sprayers, we're 100% focused on building the best sprayers in the industry.

The Apache AS1240 XP Sprayer is the highest-capacity model in the lineup. It features a 1,200-gallon tank so you spend less time refilling and more time spraying. Its mechanical drive makes it simple to operate and maintain, while nimble enough to work in field conditions competitive sprayers can't. When the days are long, its 35 mph road speed will get you to the next field (or home) faster.

### Lightweight

The AS1240 XP is engineered lightweight at just 21,000 lbs. That means better fuel economy, reduced compaction and a lower price.

### Perfect Size

This model offers a turning radius of 18 ft and a wheel base of 15 ft in — perfect for tight-fit areas.

### Affordable

Enjoy the lower cost of ownership and better resale value of an Apache. Apache Sprayers retain an average of 72 percent of their value after five years and is why the 1000 Series sprayers have won the Highest Retained Value Award from *EquipmentWatch*™ three years running.

### Unique Features of the AS1240

**Tank Capacity**  
1,200 gallons

**Transmission**  
ZF Powershift, 6-speed with lock-up torque converter

**Engine**  
Cummins Tier 4F 300 hp (rated)

**Top Road Speed**  
35 mph

**Weight**  
21,000 lbs (approximate dry weight)

**Crop Clearance**  
50" clearance with 18" drop box all-gear final drives



**APACHE**   
**SPRAYERS**

Learn more about the advantages of running with Apache! Visit your local Apache dealer or [apachesprayers.com](http://apachesprayers.com).

 877-398-6164

# The Apache Model AS1240 XP Sprayer

CHASSIS, SUSPENSION & TIRES	TANK CAPACITY	1,200 gal
	WEIGHT (APPROXIMATE DRY WEIGHT)	21,000 lbs
	AXLE WIDTH	120" fixed, 120"-160" adjustable
	TRANSPORT WIDTH & HEIGHT	144" maximum
	OVERALL LENGTH	290" maximum
	TURNING RADIUS	18'
	WHEEL BASE	15'
	FRONT TIRES (STANDARD)	Michelin® 380/80R38
	REAR TIRES (STANDARD)	Michelin 380/90R46
SPRAY OPTIONS	CROP CLEARANCE	50" clearance with 18" drop box all-gear final drives
	BOOMS	ET Custom Boom (Steel) Straight 90', 100' or 60', 90' Pommier (Aluminum) Straight 100', 120' or 132'
ENGINE & DRIVETRAIN	RINSE TANK	100 gal
	RATED HORSEPOWER	300 hp
	DRIVELINE EFFICIENCY	90%
	PTG: HP PER 1,000 lbs	12.1
	FUEL TANK CAPACITY	90 gal
	SUSPENSION	Patented independent hydraulic
	TOP ROAD SPEED	35 mph
	TRANSMISSION	ZF Powershift, 6-speed with lock-up torque converter
ENGINE	Cummins Tier 4F 300 hp (rated)	

## Common Features on All Apache Sprayer Models

CHASSIS & SUSPENSION	BRAKES	Fully enclosed, self-adjusting, internal wet disc brakes
	DEF TANK	5 gal
CAB	PRECISION APPLICATION EQUIPMENT	Raven Viper® 4+, Hawkeye®, AccuBoom™, UltraGlide AutoBoom® and RS1™ Advanced Steering
	ET CUSTOM PRESSURIZED	State-of-the-art interior and console



### FIVE-YEAR POWERTRAIN WARRANTY

Equipment Technologies warrants every new Apache Sprayer to be free from defects in materials and workmanship for a period of five years or 2,000 hours, whichever occurs first. The first two years of warranty includes bumper-to-bumper coverage (some exclusions apply), with the following three years covering parts only.

All model year 2019 Apache Sprayers are available with optional ISOBUS-ready wiring in lieu of factory installed field computers. Refer to your specific precision agriculture product documentation for compatibility information. Equipment Technologies factory installs all field computers using CAN-BUS wiring and protocols.

Equipment Technologies reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacturing at any time without notice or obligation. All brand or product names are or may be trademarks of, and are used to identify products and services of, their respective owners or its subsidiaries and divisions, in the U.S. and/or other countries. All specifications are subject to change without notice.



Learn more about the advantages of running with Apache! Visit your local Apache dealer or [apachesprayers.com](http://apachesprayers.com).

877-398-6164