GRAVELY



MODEL - 992510 27 HP / Kawasaki® FX850V Engine **MODEL - 992511**

31 HP / Kawasaki® FX921V Engine

MODEL - 992530

38.5 HP / Kawasaki® FX1000V EFI Engine

72"

MODEL - 992512

31 HP / Kawasaki® FX921V Engine

MODEL - 992531

38.5 HP / Kawasaki FX1000V EFI Engine

COMFORTABLE SEAT High back seat with isolated mounting to absorb more shock has lumbar support and padded armrests. Its red double stitching gives a high-end look with black, dark grey, and red accents. * Air Ride Seat options on

FULLY WELDED TUBULAR FRAME One glance and you can see its strength and ruggedness. Its wide front rail distributes weight for superior balance. It also supports the deck lift for easy engagement. Includes a limited lifetime warranty.

PARKER TRANSAXLES Parker HTG transaxles deliver a top speed of 15mph and have a 16cc pump. Filters are easily accessed from the rear for easy maintenance. X-FACTOR® 3 DECK Made with 7-gauge steel and specially designed for better grass dispersion thanks to its larger discharge opening, integrated baffles, and sloped front end. Reinforced spindle mounts protect blade operation while the six recessed anti-scalp wheels protect the turf on uneven terrain. Its flip-up rubber chute makes it easy to drive through gates and around obstacles. A 5/8" leading edge provides extra protection to the shell while stabilizer links keep vibration to a minimum. Includes a limited lifetime warranty.

DIAL HEIGHT ADJUSTMENT The dial wheel allows easy height adjustment between one and five inches. Toolless adjustable foot pedal with internal assist springs helps lift the deck with little effort

PRO-TURN 500



See your professional Gravely® dealer for complete warranty details.

	552	560	560	572	572
MODEL NUMBER	992510	992511	992530	992512	992531
ENGINE	KAWSAKI FX850V	KAWASAKI FX921V	KAWASAKI FX1000 EFI	KAWASAKI FX921V	KAWASAKI FX1000 EF
HORSEPOWER	27 HP	31 HP	38.5 HP	38.5 HP	31 HP
DISPLACEMENT	852 CC	999 CC	999 CC	999 CC	999 CC
DRIVE SYSTEM	PARKER HTG TRANSMISSION				
FUEL CAPACITY	12.5 GAL				
GROUND SPEED (APPROX. Mph) (Forward/ Reverse)	15 MPH / 6 MPH				
DECK					
DECK MATERIAL	7 GA. STEEL WITH .25 IN. SPINDLE REINFORCEMENT				
DECK CONSTRUCTION	X-FACTOR® 3 DECK				
NUMBER OF SPINDLES	3				
BLADE TIP SPEED (FPM)	18,000				
SPINDLE HOUSING MATERIAL	FORGED ALUMINUM				
SPINDLE BEARINGS	BALL BEARING				
DECK ENGAGEMENT	OGURA* GT3.5				
CUTTING WIDTH	52 IN.	60 IN.	60 IN.	72 IN.	72 IN.
CUTTING HEIGHTS	1.0 IN 5.5 IN.				
CUTTING POSITIONS	19				
WHEELS					
FRONT AXLE	FIXED, GREASEABLE CASTER FORK TUBES				
FRONT	SM00TH 15 X 6-6 SEMI PNEUMATIC				
REAR	26 X 12-16 RADIAL TURF				
FEATURES					
SEAT	AIR RIDE PLUSH SEAT WITH ARM RESTS				
FOLDABLE ROPS	STANDARD				
MACHINE					
WEIGHT	1447 LBS.	1487 LBS.	1580 LBS.	1477 LBS.	1580 LBS.
LENGTH		84 IN.		86.2 IN.	
WIDTH (w/o CHUTE)	51 IN.	63 IN.	63 IN.	75 IN.	75 IN.
WIDTH (w/ CHUTE)	63 IN.	75 IN.	75 IN.	87 IN.	87 IN.
HEIGHT (w/ ROPS EXT/DOWN)			76.0 IN./47.8 IN.		•
WARRANTY					
UNIT	5 YEAR/1500 HOUR COMMERCIAL/NO HOUR LIMIT FIRST 2 YEARS- SEE YOUR PROFESSIONAL GRAVELY DEALER FOR COMPLETE WARRANTY DETAILS				
DECK SHELL & FRAME	LIMITED LIFETIME				

ATTACHMENTS & ACCESSORIES

MULCHING KIT
ELECTRIC DECK LIFT KIT
TRAILER KIT KIT
LED HEADLIGHT KIT
POWERED BAGGER KIT
OCDC KIT, SUNSHADE KIT
REAR TWEEL KIT
RADIAL DRIVE CONVERSION KIT
WHEEL COVER KIT
LASEREDGE BLADE KIT
TUNE UP KIT

