



HITCH YOUR TRACTOR TO HIGH PERFORMANCE

	1 auger only					1 or 2 augers
	N78-260HE+	N86-280HE+	N92-280HDE+	N92-310HE+	N98-310HE+	N98-341HE+ N98-342HE+
Recommended horsepower (HP PTO)	40 @ 75	60 @ 85	75 @ 120	85 @ 140	85 @ 140	100 @ 160
Cutting width (in/mm)	78" 1981	86" 2184	92" 2337	92" 2337	98" 2489	98" 2489
Overall width (in/mm)	82" 2083	90" 2286	96" 2438	96" 2438	102" 2591	102" 2591
Cutting height (in/mm)	32 1/2" 826	36" 914	36" 914	38" 965	38" 965	48" 1219
Impeller RPM	540	540	540	540	540	540
Impeller diameter (in/mm)	26" 660	28 1/2" 724	28 1/2" 724	31" 787	31" 787	34" 864
Impeller depth (in/mm)	11" 279	12" 305	12" 305	14 1/4" 362	14 1/4" 362	14 1/4" 362
Number of blades	4	4	4	5	5	5
Impeller shaft diameter (in/mm)	1 9/16" 40	1 9/16" 40	2" 51	2" 51	2" 51	2" 51
Balanced impeller	Std	Std	Std	Std	Std	Std
Drum center height (in/mm)	15 1/2" 394	17 3/4" 451	17 3/4" 451	19 1/2" 495	19 1/2" 495	22" 559
Cylinder for chute (deflector) (in/mm)	2" x 6" 51 X 152	2 1/2" X 8" 64 X 203	2 1/2" X 8" 64 X 203	2 1/2" X 8" 64 X 203	2 1/2" X 8" 64 X 203	2 1/2" X 8" 64 X 203
Chute rotation by hydraulic motor	Std	Std	Std	Std	Std	Std
Hydraulic deflector	Std	Std	Std	Std	Std	Std
Manual deflector	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
Semi industrial chute (2 deflectors)	Std	Std	Std	Std	Std	Std
Hydraulic telescopic chute	-	Opt.	Opt.	Opt.	Opt.	Opt.
Hoses holder	Std	Std	Std	Std	Std	Std
Main auger diameter (in/mm)	19 1/2" 495	23" 584	23" 584	23" 584	23" 584	23" 584
Upper auger diameter	-	-	-	-	-	- / 17" 432
Balanced auger	Std	Std	Std	Std	Std	Std
Reversible carbon steel blade	Std	Std	Std	Std	Std	Std
Reversible Hardox 450 blade	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
Reversible stainless steel blade	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
Tivar blade	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
Adjustable carbon steel skid shoes	Std	Std	Std	Std	Std	Std
Adjustable Hardox 450 skid shoes	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
Adjustable stainless steel skid shoes	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
Adjustable Tivar skid shoes	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
Driving chain number	60	80	80	80	80	100
Storage foot	Std	Std	Std	Std	Std	Std
Number of safety bolts	2	2	3	3	3	3
Bearing ductile iron casing	Std	Std	Std	Std	Std	Std
Shaft P.T.O. standard	T60	T60	T80	T80	T80	T80
1 000 @ 540 reducer box	-	Opt.	Opt.	Opt.	Opt.	Opt.
Adjustable hitch	Std	Std	Std	Std	Std	Std
Hitch category (QH = quick hitch)	1, 1QH, 2	2, QH	2, QH	2, QH	2, QH	2, QH
Approx weight (lbs/kg)	1148 / 521	1847 / 838	2090 / 948	2343 / 1063	2450 / 1111	2547 / 1155 2462 / 1117

The weight includes scrapper blade but does not include chute and accessories. Specifications are subject to change without notice

oct 2020