



HITCH YOUR TRACTOR TO HIGH PERFORMANCE



**SNOWBLOWERS
HYBRID SERIES**

HYBRID SERIES



EFFICIENCY ROBUSTNESS

Hardox 450 steel components :
Structure, triple bottom, sides and reinforcements of sides, 3-points, fan, blades of the auger, lining behind the blades of auger

MOBILE LATERAL RUBBER SKID SHOES



REVERSIBLE CUTTING EDGES

- CARBON STEEL (reversible)
- STAINLESS STEEL (reversible)
- HARDOX 450 STEEL (reversible)
- TIVAR 88



WARRANTY

Every product manufactured by Normand Co. Ltd is guaranteed against manufacturing and raw material defects (excluding the P.T.O. shafts, gearboxes, engines, hydraulic motors, hydraulic cylinders, telescopic cylinders, tires, hubs and wheels, which are covered by the manufacturer warranty) for a full year from the date of purchase, provided that the product has not been modified or abused in any way. This warranty does not cover accidents or breaks caused by objects other than snow (metal bits, concrete, wood, asphalt, tires, etc.). Also blades, skid shoes, soles of skid shoes, driving chains and tires wear is not covered by the warranty. We will replace or repair any defective part at no cost if they are returned prepaid at our plant in Saint-Pascal (Kamouraska, Québec, Canada). Our obligations are limited to the replacement and/or repair of the defective part.

1 AUGER ONLY					
HYBRID SERIES	N60-240HYB	N74-250HYB	N82-260HYB	N92-280HYB	N100-310HYB
Recommended horsepower (HP PTO)	20 @ 40	25 @ 50	40 @ 75	60 @ 90	85 @ 140
Cutting width (in/mm)	60" 1524	74" 1880	82" 2083	92" 2337	100" 2540
Cutting height (in/mm)	28" 711	29" 737	30 3/4" 781	33" 838	35 3/4" 908
Impeller RPM	540	540	540	540	540
Impeller diameter (in/mm)	24" 610	25" 635	26" 660	28 1/2" 724	31" 787
Impeller depth (in/mm)	7 1/2" 191	9" 229	11" 279	12" 305	14 1/4" 362
Number of blades	4	4	4	4	5
Impeller shaft diameter (in/mm)	1 1/4" 32	1 9/16" 40	1 9/16" 40	1 9/16" 40	2" 51
Balanced impeller	Std	Std	Std	Std	Std
Drum center height (in/mm)	20 1/4" 514	21 1/2" 521	22 1/2" 572	24 1/4" 616	26 1/2" 673
Chute rotation by hydraulic motor with valve (gear)	Std	Std	Std	Std	Std
Semi industrial chute (2 deflectors)	Std	Std	Std	Std	Std
Hydraulic deflector	Std	Std.	Std.	Std	Std
Manual deflector	Opt.	Opt.	Opt.	Opt.	Opt.
Cylinder for chute deflector (in/mm)	2" X 4" 51 X 102	2" X 4" 51 X 102	2" X 6" 51 X 152	2 1/2" X 8" 64 X 203	2 1/2" X 8" 64 X 203
Main auger diameter (in/mm)	14" 356	15" 381	16" 406	17" 432	18" 457
Balanced auger	Std	Std	Std	Std	Std
Reversible carbon steel blade	Std	Std	Std	Std	Std
Reversible Hardox 450 blade	Opt	Opt.	Opt.	Opt.	Opt.
Reversible stainless steel blade	Opt	Opt.	Opt.	Opt.	Opt.
Tivar blade	Opt	Opt.	Opt.	Opt.	Opt.
Mobile lateral rubber skid shoes	Std	Std	Std	Std	Std
Storage foot	Std	Std	Std	Std	Std
Hoses holder	Std	Std	Std	Std	Std
Driving chain number	60	60	80	80	100
Chain guard	Std	Std	Std	Std	Std
Number of safety bolts	2	2	2	3	3
Key for driving shaft adjustment	Std	Std	Std	Std	Std
Bearing ductile iron casing	Std	Std	Std	Std	Std
PTO shaft standard	T20	T40	T60	T60	T80
Hitch category (QH = Quick Hitch)	1, 1QH	1, 1QH	1, QH, 2	2, 2QH	2, 2QH
Approx weight (lb/kg) - 1 auger	860 / 390	1063 / 482	1265 / 574	1709 / 775	2256 / 1023

The weight includes chute, hydraulic cylinder for chute deflector, rotation kit and PTO
Specifications subject to change without notice.



Normand Co. Ltd
340, Tache Street
Saint-Pascal (Quebec) Canada G0L 3Y0
T : 418 492-2712
1 888 666-7626
F : 418 492-9363
E-mail : normand@cienormand.com

www.cienormand.com
www.facebook.com/cienormand



DEALER