

GENERAL SPECIFICATIONS

MODELS	248M	458M	869M	12712M
Capacity	2 Tons	4 Tons	8 Tons	12 Tons
Weight	875 lbs	1 395 lbs	2 580 lbs	4 750 lbs
Capacity Cu. ft. / extension	42,5 Cu. Ft.	62,5 Cu. Ft.	98 / 129 Cu. Ft.	152 / 277 Cu. Ft.
Capacity Cu. yard	1,6 Cu. Yard	2,3 Cu. Yard	3,63 / 4,78 Cu. Yard ***	5,63 / 10,25 Cu. Yard ***
Recommended extension	2" x 4"	2" x 6"	2" x 6"	2" x 6" (3x)
Load surface	47 1/2" x 94"	59" x 100 1/2"	71 1/2" x 106"	86 1/2" x 141 1/2"
Floor plate	12 ga.	11 ga.	1/4"	1/4"
Overall width	52 1/2"	64 5/8"	77 1/2"	92 1/4"
Side panel	10"	12"	16"	22"
Front and rear panel	17" / 13 1/4"	17 7/8" / 17 1/4"	23"	40"
Height platform to ground	26"	34"	35 1/2"	47"
Overall length	132 7/8"	154"	162"	212"
Tread	40 1/4"	50"	59"	72"
Spindle	1 5/8"	1 3/4"	2 1/4"	3"
Axle	Tandem	Tandem	tandem	tandem
Hub (bolt qty)	5	5	6	8
Hub capacity	1 250 lbs	2 500 lbs	6 000 lbs	10 000 lbs
Tandem spindle bolt	1 1/4"	1 1/4"	1 3/4"	2"
Wheel and tire	Wheels 6" x 10" Tires 20,5 x 8 - 6 Ply	Wheels 6" x 15" Tires ST205/75 D15	Wheels 8" x 15" 11L15 - 8 Ply utility	Wheels W14C 16,5"x16,1" - 10 Ply
Overall height	45"	58"	66 1/2"	87 1/2"
Wheel and tire	-	Wheels 6" x 15" Tires 7,80 x 15 - 8 Ply	-	Wheels 11,75" x 22,5" 425/65R22,5 (used mixer tires)
Overall height	-	58 7/8"	-	89 1/2"
Wheel and tire	-	-	-	Wheels 16" x 22,5" 550/45R22,5-16 Ply (Flotation)
Overall height	-	-	-	88 1/4"
Off-center beam shaft	Standard	Standard	Standard	Standard
Automatic opening and closing rear panel	Standard	Standard	Standard	Standard
Cylinder size	3" x 16"***	3 1/2" x 24"***	4" x 24"***	Tel. 3 sections
Cylinder type	1 double action	1 double action	1 double action	1 single action
Dumping angle	47°	46,5°	49°	50°
Coupling height	15 1/2"	19 1/2"	19 1/2"	21 1/2"
Free height - lifted up	8 1/2"	18 1/4"	15 1/4"	27"
Grain door	-	-	-	Standard
Swivel coupler (clevis)	Standard	Standard	Standard	Standard
Electric brakes	-	Option	option	-
Hydraulic brakes	-	-	-	option
Mechanical jack	Standard	Standard	Standard	Standard
Manual pump (dump box)	Option	Option	-	-
Electrical pump (dump box)	Option	Option	option	-

** Cylinder under platform *** Recommended wood extension
N.B. : Specification subject to change without notice, without obligation



NORMAND WARRANTY

Every product manufactured by Normand Co. Ltd is guaranteed against manufacturing and raw material defects (excluding the P.T.O. shafts, gearboxes, engines, hydraulic motors, hydraulic cylinders, telescopic cylinders, tires, hubs and wheels, which are covered by the manufacturer warranty) for a full year from the date of purchase, provided that the product has not been modified or abused in any way. This warranty does not cover accidents or breaks caused by objects other than snow (metal bits, concrete, wood, asphalt, tires, etc.). Also blades, skid shoes, soles of skid shoes, driving chains and tires wear is not covered by the warranty. We will replace or repair any defective part at no cost if they are returned prepaid at our plant in Saint-Pascal (Kamouraska, Québec, Canada). Our obligations are limited to the replacement and/or repair of the defective part.



Normand Co. Ltd
 340, Tache Street
 Saint-Pascal (Quebec) Canada G0L 3Y0

T : 418 492-2712
1 888 666-7626
F : 418 492-9363

E-mail : normand@cienormand.com

www.cienormand.com

www.facebook.com/cienormand



Some illustrations may include options. The illustrations, features and weights are approximate and without commitment. We reserve the right to make all changes for improvement.

DEALER

© Normand® Co. Ltd 2019 All Rights Reserved