

HD HYDRAULIC SNOWBLOWER



Models 6025, 6035, 7225, 7235, 8425, 8435





The Allied by Farm King HD Hydraulic Snowblowers have been engineered to maximize your skid steers efficiency. Available in high and low flow configurations, Allied by Farm King blowers will connect with any modern skid steer. Designed to be durable and reliable Allied by Farm King products are the best choice for industrial and commercial snow removal.



Hydraulic Motors

Allied by Farm King hydraulic drive snowblowers have hydraulic motors mounted directly on the fan and auger shaft eliminating couplers and chain drive assemblies for simplicity and ease of maintenance. A hydraulic relief replaces traditional shear pin technology for increased productivity and reduced downtime.



Wiring Harness

The Allied by Farm King hydraulic drive snowblower series have a wiring harness to fit almost any brand on the market. Compatibility available with: Bobcat 14 pin, Cat "B / C" series 8 pin, Case / New Holland 14 pin and John Deere 14 pin. A magnetic cab mounted control box is available on all other models.



Hydraulic Motor Chain Drive Assembly

With a hood turning range of 270° Allied by Farm King hydraulic drive snowblowers give you superior control when moving snow.



For more information contact:
E-mail: info@buhler.com
www.farm-king.com

Equipment shown is subject to change without notice.
©2015 Buhler Trading Inc. Printed in Canada.

bühler | a division of Buhler Industries Inc.

MODEL	6025	6035	7225	7235	8425	8435
Cutting width	60"	60"	72"	72"	84"	84"
Cutting height	25"	25"	35"	35"	35"	35"
Mount plate	Universal	Universal	Universal	Universal	Universal	Universal
Hydraulic requirements	17 - 23 GPM	23 - 36 GPM	17 - 23 GPM	23 - 40 GPM	17 - 23 GPM	23 - 40 GPM
Throwing distance	Up to 40'	Up to 30'	Up to 40'	Up to 40'	Up to 40'	Up to 40'
Fan	4-blade	4-blade	4-blade	4-blade	4-blade	4-blade
Fan diameter	20"	20"	20"	24"	20"	24"
Auger diameter	14"	14"	14"	18"	14"	18"
Drive auger	Hydraulic motor	Hydraulic motor	Hydraulic motor	Hydraulic motor	Hydraulic motor	Hydraulic motor
Chute rotation	270°	270°	270°	270°	270°	270°
Chute deflector	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic
Cutting edge	½" x 4" bolt-on	½" x 4" bolt-on	½" x 4" bolt-on	½" x 4" bolt-on	½" x 4" bolt-on	½" x 4" bolt-on
Skid shoes	Adjustable and replaceable	Adjustable and replaceable	Adjustable and replaceable	Adjustable and replaceable	Adjustable and replaceable	Adjustable and replaceable
Weight	828 lb	828 lb	923 lb	1084 lb	951 lb	1108 lb