

NORMAND	1 auger only (LP)								1 or 2 augers	1 auger only (LP)
	N54-220	N60-220	N68-240 N68-240TR	N74-240 N74-240TR	N74-260C	N82-260H N82-260HTR	N86-260 N86-260TR	N86-280H N86-280HTR	N86-282H N86-282HTR	N92-280H
Recommended horsepower (HP PTO)	20@40*	20@40*	25@40	25@40	40@65	40@75	50@75	60@85	60@85	60@85
Cutting width	54"	60"	68"	74"	74"	82"	86"	86"	86"	92"
Cutting height	28 1/4"	28 1/4"	30 1/4"	30 1/4"	32 3/4"	32 1/2"	36"	36"	41"	36"
Impeller RPM	540	540	540	540	540	540	540	540	540	540
Impeller diameter	22"	22"	24"	24"	26"	26"	26"	28 1/2"	28 1/2"	28 1/2"
Impeller depth	8"	8"	9"	9"	11"	11"	11"	12"	12"	12"
Number of blades	4	4	4	4	4	4	4	4	4	4
Impeller shaft diameter	1 1/4"	1 1/4"	1 9/16"	1 9/16"	1 9/16"	1 9/16"	1 9/16"	1 9/16"	1 9/16"	1 9/16"
Balanced impeller	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std
Drum center height	15"	15"	15 1/2"	15 1/2"	15"	15 1/2"	18 1/2"	17 3/4"	17 3/4"	17 3/4"
Removable rotary drum	-	-	- / Std	- / Std	-	- / Std	- / Std	- / Std	- / Std	-
Cylinder for chute (deflector)	2" X 4"	2" X 4"	2" X 4"	2" X 4"	2" X 4"	2" X 6"	2 1/2" X 8"	2 1/2" X 8"	2 1/2" X 8"	2 1/2" X 8"
Chute rotation by hydraulic motor (gear with cushion valve)	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std
Manual deflector	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std
Hydraulic deflector	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
Semi industrial chute (2 deflectors)	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std
Hydraulic telescopic chute	-	-	-	-	-	-	Opt.	Opt.	Opt.	Opt.
Hoses holder	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std
Main auger diameter	17"	17"	17"	17"	19 1/2"	19 1/2"	23"	23"	23"	23"
Upper auger diameter	-	-	-	-	-	-	-	-	-	13"
Balanced auger	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std
Reversible carbon steel blade	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std
Reversible Hardox 450 blade	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
Reversible stainless steel blade	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
Tivar blade	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
Lateral blades	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
Adjustable carbon steel skid shoes	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std
Adjustable Hardox 450 skid shoes	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
Adjustable stainless steel skid shoes	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
Adjustable Tivar skid shoes	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
Driving chain number	60	60	60	60	60	60	80	80	80	80
Storage foot	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std
Number of safety bolts	2	2	2	2	2	2	2	2	2	2
Bearing ductile iron casing	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std
Shaft P.T.O. standard	T20	T20	T40	T40	T60	T60	T60	T60	T60	T60
1 000 @ 540 reducer box	-	-	-	-	-	-	-	Opt.	Opt.	Opt.
Adjustable hitch	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std
Hitch category (QH = quick hitch)	1	1	1	1	1	1, 1 QH, 2	2	2, QH	2, QH	2, QH
Approx. weight (lb) - 1 auger	570	610	650 820	685 835	860	950 1 060	1 265 1 420	1 387 1 522	1 461 1 596	1 414

➤ The weight does not include chute and accessories. Specifications are subject to change without notice.

NORMAND	1 auger only (LP)		1 or 2 augers	1 auger only (LP)				1 or 2 augers			
	N92-280HD N92-280HDTR	N92-310	N92-312H N92-312HTR	N98-280H	N98-310H N98-310HTR	N98-340H	N102-340H	N98-312H N98-312HTR	N98-342H N98-342HTR	N102-342H N102-342HTR	N112-342H N112-342HTR
Recommended horsepower (HP PTO)	75@120	85@140	85@140	75@120	85@140	100@160	100@160	85@140	100@160	100@160	100@160
Cutting width	92"	92"	92"	98"	98"	98"	102"	98"	98"	102"	112"
Cutting height	36"	38"	41 1/2"	36"	38"	41 1/8"	41 1/8"	41 1/2"	48"	48"	48"
Impeller RPM	540	540	540	540	540	540	540	540	540	540	540
Impeller diameter	28 1/2"	31"	31"	28 1/2"	31"	34"	34"	31"	34"	34"	34"
Impeller depth	12"	14 1/4"	14 1/4"	12"	14 1/4"	14 1/4"	14 1/4"	14 1/4"	14 1/4"	14 1/4"	14 1/4"
Number of blades	4	5	5	4	5	5	5	5	5	5	5
Impeller shaft diameter	2"	2"	2"	2"	2"	2"	2"	2"	2"	2"	2"
Balanced impeller	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std
Drum center height	17 3/4"	19 1/2"	19 1/2"	17 3/4"	19 1/2"	21"	21"	19 1/2"	21"	21"	21"
Removable rotary drum	- / Std	-	- / Std	-	- / Std	-	-	- / Std	- / Std	- / Std	- / Std
Cylinder for chute (deflector)	2 1/2" X 8"	2 1/2" X 8"	2 1/2" X 8"	2 1/2" X 8"	2 1/2" X 8"	2 1/2" X 8"	2 1/2" X 8"	2 1/2" X 8"	2 1/2" X 8"	2 1/2" X 8"	2 1/2" X 8"
Chute rotation by hydraulic motor (gear with cushion valve)	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std
Manual deflector	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std
Hydraulic deflector	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
Semi industrial chute (2 deflectors)	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std
Hydraulic telescopic chute	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
Hoses holder	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std
Main auger diameter	23"	23"	23"	23"	23"	23"	23"	23"	23"	23"	23"
Upper auger diameter	-	-	13"	-	-	-	-	13"	17"	17"	17"
Balanced auger	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std
Reversible carbon steel blade	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std
Reversible Hardox 450 blade	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
Reversible stainless steel blade	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
Tivar blade	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
Lateral blades	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
Adjustable carbon steel skid shoes	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std
Adjustable Hardox 450 skid shoes	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
Adjustable stainless steel skid shoes	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
Adjustable Tivar skid shoes	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
Storage foot	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std
Driving chain number	80	80	80	80	80	100	100	80	100	100	100
Number of safety bolts	3	3	3	3	3	3	3	3	3	3	3
Bearing ductile iron casing	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std
Shaft P.T.O. standard	T80	T80	T80	T80	T80	T80	T80	T80	T80	T80	T80
1 000 @ 540 reducer box	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.	Opt.
Adjustable hitch	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std	Std
Hitch category (QH = quick hitch)	2, QH	2, QH	2, QH	2, QH	2, QH	2, QH	2, QH	2, QH	2, QH	2, QH	2, QH
Approx. weight (lb) - 1 auger	1 630 1 669	1 753	1 797 1 969	1 669	1 883 2 073	1 976	2 001	1 914 2 107	2 048 2 193	2 071 2 215	2 175 2 320

➤ The weight does not include chute and accessories. Specifications are subject to change without notice