

800.437.6912

STUMP GRINDER *skid steer attachment*

ERSKINE

DON'T GET STUMPED YOU NEED OF ONE THESE ...

The Stump Grinder is the choice for arborists, large contractors, landscapers and maintenance departments. Mounted on a skid steer, these units are easy to maneuver into tight areas that would be impossible to reach with other types of machines without creating unnecessary damage to property. It features the ideal combination of maneuverability, power, durability, and simplicity.

FEATURES

- Bidirectional cutting design allows for dual pass operation without moving skid steer
- 32 durable carbide teeth a real time saver, reduces labor
- 1/2" x 24" diameter steel plate cutting wheel
- No gear box
- Up to 1,100 RPM cutting wheel speed
- Maximum cutting depth 8" below ground

800.437.6912



ERSKINE ATTACHMENTS LLC www.erskineattachments.com 800.437.6912

STUMP GRINDER *skid steer attachment*



Offset wheel allows operator better visibility. Quick Stump-Away's hydraulic motor powers the 1/2" steel cutting wheel to an impressive 1100 rpm.



The Quick Stump-Away's unique bi-directional cutting design creates a more aggressive cutting pattern, quickly chewing through the stump.

Model	Standard Flow	High Flow		Options
Part Number	900550	900551		Full Set of Replacement Teeth
Operating Weight	540 lb.	540 lb.		Replacement Threaded Tooth Holder
Direct Drive	No Gear Box	No Gear Box		5/8" x 2" Recessed Holder Bolt
Hydraulic Requirements	15-30 GPM	31-42 GPM		Pistol Grip Control Harness
Maximum Cutting Diameter	32"	32"	in and in the	Loader Specific Wire Harness
Maximum Cutting Depth	8" Below Ground	8" Below Ground		Factory Installed Case Drain Coupler
Cutting Arc	55°	55°		Factory Installed Couplers
Cutting Wheel Diameter	24"	24"		Factory Installed High Flow Coupler
Cutting Wheel Speed	590-1,100 RPM	900-1,200 RPM		All section of the section of the
Teeth (carbide)	32 Replaceable Carbide	32 Replaceable Carbide		
Case Drain	N/A	Required		

800.437.6912



Sec



STUMP GRINDER *skid steer attachment*

DRIVE SYSTEM - is electric over hydraulic

GUARD ASSEMBLY and RUBBER DEFLECTOR prevent flying debris



ERSKINE

is fitted with carbide teeth for durability and speed

24" diameter, 1/2" STEEL CUTTING WHEEL



Optional: Pistol Grip Control Harness is required if skid steer is NOT equipped with attachment control system. (Only needed when ordering hydraulic angling model).



Carbide teeth aggressively chew through any size stump with little wear.



Up to 1,100 RPM cutting wheel speed to grind stumps in no time!

800.437.6912

