

HYDRAULIC THUMB ON AXLE SUPPORT

POB SERIES



PROS

Choice of 2-4 fingers

130° rotation

For excavators from 1.5 to 40 tons

XHD Cylinder included

TECHNICAL SPECIFICATIONS

GENERAL OVERVIEW

HYDRAULIC THUMB ON AXLE SUPPORT

Fixed on the axle support, this thumb design follows the rotation of your bucket and allows maximum yield when performing your work to ease all your work, regardless of the task ahead. Our improved designs allows you to maintain good visibility and is easily adaptable to your quick-coupler and bucket. It's also available in different size, for any type of excavator.

FEATURES

XHD Hydraulic Cylinder

- Bolt-on head.
- Hydraulic cylinder intergrated stroke absorber.
- Oversized rod for intensive work.

Hardened and greasable bearing

- 2 bearing included.

TECHNICAL SPECIFICATIONS

WEIGHT (TONNES)	CLASS	LENGHT (IN)	NUMBER OF FINGERSS	WEIGHT (LB)
1.5 - 2.2	15	20	2/4	65
2.3 - 3.9	35	25	2/4	150
4.0 - 5.9	50	30	2/4	200
6.0 - 9.9	75	36	2/4	450
10 - 15	120	52	2/4	915
16 - 19	160	58	2/4	1 035
19 - 23	200	60	2/4	1 480
20 - 23	240	60	2/4	1 520
24 - 29	270	63	2/4	1 750
30 - 39	300	68	2/4	2 125
40 - 49	400	68	2/4	2 920



* Other models and sizes available on request.

COMPATIBILITY

- | | | |
|--------------|---------------|---------------|
| ✓ Bobcat | ✓ Case | ✓ Caterpillar |
| ✓ Doosan | ✓ Hitachi | ✓ Hyundai |
| ✓ John Deere | ✓ Kobelco | ✓ Komatsu |
| ✓ Kubota | ✓ Liebherr | ✓ Link-Belt |
| ✓ Mustang | ✓ New Holland | ✓ Takeuchi |
| ✓ Terex | ✓ Volvo | ✓ Yanmar |

OPTIONS

- Choice of 2, 3 or 4 fingers