



SKIDDING WINCH

WALLENSTEIN

**FX
FXP**

**SKIDDING WINCH
SKIDDING PLATE**

3-POINT HITCH



**IT'S A WHOLE
NEW LINE-UP**





SKIDDING WINCH



NAVIGATE THE FARTHEST REACHES OF YOUR FOREST

Managing the full potential of your forest is easy with the pulling strength of the Bush Pilot Skidding Winch. You can now reach the trees you need to cut, even on steep hills or swampland without the need for large heavy equipment. For tractors 15 – 140 hp, the new Bush Pilot builds on Wallenstein's strong reputation of skidding winches with pulling strength up to 14,000-lbs and reach up to 165 feet.



UP TO
14,000 LBS
OF PULLING STRENGTH



UP TO
165 FEET
OF CABLE LENGTH



**KEYHOLE SLIDERS
PULL UP TO 3 LOGS**



**OPTIONAL
SYNTHETIC ROPE**



**OPTIONAL
REMOTE CONTROL**

SKIDDING WINCH



**OPTIONAL
SELF-RELEASING
SNATCH BLOCK PULLY**



**WORK
WORRY-
FREE WITH
WALLENSTEIN**

You work hard and we've got you covered worry-free with a 5 Year Consumer Warranty that comes with every new Wallenstein product.

For details, visit www.embmfg.com.



FX

SKIDDING WINCH

SKIDDING WINCH



STANDARD FEATURES

1 choker chain

Hydraulic 2-Speed Winch



STANDARD FEATURES

Keyhole Slots

Winch Cable End

Keyhole Sliders

Rope Controlled brake/clutch system



FX35

- 3,500 lb Pulling Capacity
- 15 - 30 Recommended HP
- Category 1 3PH Mount
- 22-260 ft./min.
- 80' of 5/16" Synthetic Rope
- 1 Choker Chain
- Weight: 245 lbs
- Dimensions: 27" x 40" x 48"
- Two Speed Hydraulic Winch*
- * Requires 2-12 GPM, Optimum 6 GPM



FX66

- 6,600 lb Pulling Capacity
- 30 - 60 Recommended HP
- Category 1 3PH Mount
- 540 RPM Max PTO Input Speed
- 96-238 ft./min. Cable Speed at 540 RPM
- 165' of 3/8" Cable
- Mechanical, Dry Disk Clutch
- Weight: 450 lbs
- Dimensions: 19" x 40" x 71"
- * Keynote sliders not included with FX66



FX85

- 8,500 lb Pulling Capacity
- 30 - 60 Recommended HP
- Category 1 3PH Mount
- 540 RPM Max PTO Input Speed
- 96-238 ft./min. Cable Speed at 540 RPM
- 165' of 3/8" Cable
- 2 Choker Chain
- Mechanical, Dry Disk Clutch
- Weight: 470 lbs
- Dimensions: 27" x 40" x 76"
- Optional Bolt-On Remote Control Kit (Part# F200)
- FX85R Includes Factory Installed Remote Control Kit **



SKIDDING WINCH

OPTIONAL FEATURES

Removable Clutch Assembly

Trailer Hitch
(Not available on FX66)

PTO Drive

Synthetic Rope

Self Releasing Snatchbox Pulley

Remote Control



FX110

- 11,000 lb Pulling Capacity
- 45 - 100 Recommended HP
- Category 1 & 2 3PH Mount
- 540 RPM Max PTO Input Speed
- 98-253 ft./min. Cable Speed at 540 RPM
- 165' of 7/16" Cable
- 2 Choker Chain
- Mechanical, Dry Disk Clutch
- Weight: 796 lbs
- Dimensions: 28" x 50.5" x 79"
- Optional Bolt-On Remote Control Kit (Part# F200)
- FX110R Includes Factory Installed Remote Control Kit **

FX140

- 14,000 lb Pulling Capacity
- 60 - 140 Recommended HP
- Category 1 & 2 3PH Mount
- 540 RPM Max PTO Input Speed
- 98-246 ft./min. Cable Speed at 540 RPM
- 165' of 1/2" Cable
- 2 Choker Chain
- Mechanical, Dry Disk Clutch
- Weight: 898 lbs
- Dimensions: 28" x 58.5" x 80"
- Optional Bolt-On Remote Control Kit (Part# F200)
- FX140R Includes Factory Installed Remote Control Kit **

** Remote kit requires 12V from tractor, 1-2 GPM hydraulic flow from tractor. The winch is pre-set at 700 psi



STANDARD FEATURES

Four Chain Holder Slots

Capable of handling multiple logs at one time, the FXP reduces the drag surface by lifting the front end of the logs. This gives you better control when turning, as the log acts like a trailer. The optional Choker Chains and Log Tongs are both ideal tools for quick hookup.

Removable Hitch



Colors Available

OPTIONAL FEATURES

Log Tongs

Choker Chains

FXP30

- Cat. 1 & 2, 3 PH Mounting
- 2 Saddle Grab Hooks
- 2" Receiver for Ball Mount Towbar
- Weight 216 lbs. (Uncrated)
- Dimensions:
Uncrated (LxWxH) 44" x 25" x 44"
Crated (LxWxH) 44" x 25" x 44"
- Up to 80 hp Recommended Range

FXP20

- Cat. 1, 3 PH Mounting
- 1 Saddle Grab Hooks
- 2" Receiver for Ball Mount Towbar
- Weight 98 lbs. (Uncrated)
- Dimensions:
Uncrated (LxWxH) 35" x 12" x 32"
Crated (LxWxH) 38" x 32" x 18"
- Up to 40 hp Recommended Range

Skidding Winch Options

Remote Control Winch Kit

Part#	Description
F200	<ul style="list-style-type: none"> • FX85 & FX110 Remote Control Transmitter range = 300ft (100 metres) • Remote requires 12 volts and 1-2 g.p.m. Hydraulic flow from tractor • Not available for FX35, FX66
F205	<ul style="list-style-type: none"> • FX140 Remote Control Transmitter range = 300ft (100 metres) • Remote requires 12 volts and 1-2 g.p.m. Hydraulic flow from tractor • Not available for FX35, FX66

Wallenstein uses Pioneer style ball type hydraulic couplings for all tractor auxiliary connections. Substitutions are not available from Wallenstein and must be made at the customers expense.

Self Releasing Snatch Block

Part#	Description
5089A100	<ul style="list-style-type: none"> • Helps with winching duties

Synthetic Choker

Part#	Description
Z92125	• 5 ft Synthetic Choker with Rod Chain End
Z92126	• 7 ft Synthetic Choker with Rod Chain End

Synthetic Rope

Part#	Description
Z92124	• 200 ft 1/2" Synthetic Mainline with Hook Chain End (FX110, FX140)
Z92123	• 200 ft 7/16" Synthetic Mainline with Hook Chain End (FX66, FX85)

Colour Options



When ordering, please use 3 letter colour designation behind models

Skidding Plate Options

Logging Tongs

Part#	Description
Z99003	<ul style="list-style-type: none"> • Opens to approx 26 inches • for use with skidding blade only

Choker Chain

Part#	Description
Z92318	• 90" choker chain with sliding hook

Colour Options



When ordering, please use 3 letter colour designation behind models