

HIGH DUMP BUCKET

GLI SERIES



PROS

Oversized rod for intensive work

Dump angle up to 120°

High capacity

Ideal for light materials such as woodchips, sand, etc.

TECHNICAL SPECIFICATIONS

GENERAL OVERVIEW

HIGH DUMP BUCKET

This bucket is the most versatile attachment for light and multi-purpose work. It boasts two hydraulic cylinders, enabling a 120 ° effortless release. Damping pads are installed to minimize impact on return to the working position.

FEATURES

Damping pads

Rubber pads (2) act as shock absorbers when resuming original position after release.

HD hydraulic cylinder

- Integrated travel damper.
- Oversized rod for intensive work.

Bolted-on blade

Optional bolted-on blade

Dumping angle

The maximum dumping angle is 120°.

TECHNICAL SPECIFICATIONS

CLASS	WIDTH (IN)	CAPACITY (VC)
Backhoe loader	92	2.00
10	89	2.50
20	100	3.00
30	100	5.00
40	100	5.50
50	118	6.00
60	125	8.00
70	144	10.00



** Other models and sizes available on request.*

COMPATIBILITY

- ✓ Bobcat
- ✓ Doosan
- ✓ JCB
- ✓ Komatsu
- ✓ Manitou
- ✓ Volvo
- ✓ Case
- ✓ Ford
- ✓ John Deere
- ✓ Kubota
- ✓ New Holland
- ✓ Caterpillar
- ✓ Hyundai
- ✓ Kawasaki
- ✓ Liebherr
- ✓ Terex

OPTIONS

- Bolted and interchangeable blade optional.