§MAVERICK™ X3 X™mr TURBO R

HIGHLIGHTS

DEFIANT

- Trademark Can-Am DNA with next generation design
- Low seating position
- Ergo-Lok cockpit with fourway adjustable seats

POWERFUL

- Industry leading 172 hp turbocharged and intercooled Rotax® ACE engine Advanced airflow dynamics
- QRS-X transmission

PRECISE

- TTX suspension with industry
- leading travel
 Ultra efficient and
 lightweight chassis
- Sharpest handling features

Carbon Black & Sunburst Yellow / TURBO R

SPECIFIC TO X mr PACKAGE

- 72-in. (182.9 cm) wide
- Strategically positioned engine air intake and CVT air intakes / exhaust Smart-Lok[™]* Full lockable on-the-fly front differential with electronically-controlled automatic
- 14-in. aluminum beadlock wheels with 30-in. ITP Cryptid tires

- Up to 24-in. of suspension travel

 FOX† 2.5 PODIUM Piggyback shocks with QS3† compression adjustment

 4,500-lb (2,041kg) winch with synthetic rope

 Front bumper, full High Molecular Weight (HMW) skid plate, under bumper skid plate, half-doors, front and rear tow hooks

ENGINE	TURBO R
Туре	172 hp, Rotax ACE (Advanced Combustion Efficiency) 900 cc Turbocharged Triple-cylinder engine, liquid cooled with integrated intercooler, Donaldson† high-perfomance air filter and strategically positioned engine air intake
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	Quick Response System X (QRS-X) CVT, high airflow with strategically positioned CVT air intakes and exhaust, L / H / N / R / P
Drive Train	Lockable front differential with exclusive Smart-Lok* technology. True 4 modes traction system: 2WD / 4WD with front diff. lock / 4WD MUD / 4WD TRAIL *Smart-Lok was developed in conjunction with TEAM Industries, a market leader in the drive train industry
Power Steering	High torque Tri-Mode Dynamic Power Steering (DPS™)
SUSPENSIONS	
Front Suspension	Double arched A-arm with sway bar 22-in. (55.9 cm) travel / Trophy truck inspired arms
Front Shocks	FOX† 2.5 PODIUM Piggyback with QS3† compression adjustment
Rear Suspension	4-link Torsional Trailing-arm X (TTX) with sway bar and arched lower links, 24-in. (61 cm) travel
Rear Shocks	FOX† 2.5 PODIUM Piggyback with QS3†compression adjustment and bottom-out control
BRAKES	
Front	Dual 262 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 248 mm ventilated disc brakes with hydraulic twin-piston calipers

TIRES / WHE	ELS
Front Tires	ITP Cryptid 30 x 9 x 14 in. (76.2 x 22.9 x 35.6 cm)
Rear Tires	ITP Cryptid 30 x 11 x 14 in. (76.2 x 27.9 x 35.6 cm)
Wheels	14-in. (35.6 cm) cast-aluminum with

DIMENSIONS / CAPACITIES		
LxWxH	133 x 74.7 x 66.1 in. (337.8 x 189.7 x 167.9 cm)	
Wheelbase	102 in. (259.1 cm)	
Ground Clearance	15 in. (38.1 cm)	
Estimated Dry Weight	1,689 lb (766.1 kg)	
Cage / Chassis	Dual-phase 980 steel, fully welded	
Rack Capacity	200 lb (91 kg) with LinQ™ quick- attach	
Storage Capacity	Total: 2.5 gal (9.4 L) Glove box: 1.6 gal (6.2 L) Central console: 0.8 gal (2.8 L) Cup holders: 0.1 gal (0.4 L)	

FEATURES			
Gauge	Multifunction Analog / Digital: Speedometer, tachometer, odometer, trip and hour meters, fuel, gear position, sport / ECO™ mode, seat belt and 4 x 4 indicator, diagnostics, clock, auto shut off	Protection	Front bumper, full High Molecular Weight (HMW) skid plate, under bumper skid plate, half-doors, front and rear tow hooks
		Instrumentation	Lighter type DC Outlet in central console
		Lighting	LED headlights and tail lights with unique Can-Am LED signature
Winch	4,500-lb (2,041 kg) winch with synthetic rope	Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™) with Start/ Stop button

WARRANTY	
Factory	6-months limited warranty
Extended	Up to 30 months B.E.S.T. coverage





