©OUTLANDER™ XT 570

HIGHLIGHTS

- Rotax® V-Twin engine
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS™)
- 3,000-lb (1,361 kg) WARN[†] winch with roller fairlead
- Painted plastics for premium look
- · Heavy-duty front and rear bumpers
- 12-in. cast-aluminum wheels
- 25-in. Maxxis† M923J radial tires
- Double A-arm front suspension
- Torsional Trailing arm Independent (TTI) rear suspension
- Wind deflectors

- 500-W magneto
- Steel racks with LinQ quick-attach accessory system and a combined 360 pounds (163.3 kg) capacity
- 2.9-gal (10.9 L) water-resistant rear compartment



| ENGINE | 570 |
|----------------------|---|
| Туре | 48 hp, Rotax 570 cc V-twin, liquid cooled |
| Fuel Delivery System | Electronic Fuel Injection (EFI) |
| Transmission | CVT, P / R / N / H / L, standard engine braking |
| Drive Train | Selectable 2WD / 4WD with Visco-Lok [‡] QE auto-locking front differential |
| Power Steering | Tri-Mode Dynamic Power Steering (DPS) |

| TIRES / WHEELS | 3 |
|----------------|--|
| Front Tires | Maxxis M923J 25 x 8 x 12 in. (63.5 x 20.3 x 30.5 cm) |
| Rear Tires | Maxxis M923J 25 x 10 x 12 in. (63.5 x 25.4 x 30.5 cm) |
| Wheels | 12-in. cast-aluminum |

| Double A-arm 9 in. (22.9 cm) travel |
|--|
| Oil |
| Torsional Trailing arm Independent (TTI) 8.8 in. (22 cm) travel |
| 0il |
| |

| DIMENSIONS / CAPACITIES | | |
|-------------------------|--|--|
| LxWxH | 83 x 46 x 49 in. (211 x 116.8 x 124 cm) | |
| Wheelbase | 51 in. (129.5 cm) | |
| Ground Clearance | 10.5 in. (26.7 cm) | |
| Seat Height | 33.8 in. (85.8 cm) | |
| Dry Weight | 704 lb (319 kg) | |
| Rack Capacity | Front: 120 lb (54.4 kg) Rear: 240 lb (109 kg) | |
| Storage Capacity | Rear: 2.9 gal (10.9 L) | |
| Towing Capacity | 1,300 lb (590 kg) | |
| Fuel Capacity | 5.4 gal (20.5 L) | |

| BRAKES | |
|--------|--|
| Front | Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers |
| Rear | Single 214 mm ventilated disc brake with hydraulic twin-piston caliper |

| FEATURES | | | |
|------------|--|-------------------|--|
| Gauge | Multifunction Digital: Speedometer, tachometer, odometer, | Instrumentation | Lighter type DC outlet in console, standard connector in the back (15-A) |
| | trip & hour meters, fuel, gear position, 4 x 4 indicator, diagnostics, clock | Lighting | 70 W from dual 35-W front light / brake light |
| Winch | 3,000-lb (1,361 kg) WARN winch with roller fairlead | Seat | Standard |
| Protection | Heavy-duty front & rear bumpers Handlebar wind deflectors | Anti-theft System | N/A |

| WARRANTY | |
|----------|-----------------------------------|
| Factory | 6-months limited warranty |
| Extended | Up to 36 months B.E.S.T. coverage |

