

# 2019 RENEGADE® ADRENALINE

## PACKAGE HIGHLIGHTS

- Rotax® 850 E-TEC®, 600R E-TEC®, 900 ACE™ Turbo and 900 ACE™ engines
- RAS™ 3 front suspension
- REV® Gen4 platform with narrow-design (E-TEC® engines) or **wide-design (ACE™ engines)** bodywork
- pDrive™ clutch
- Ergo-Step side panels
- Open toe-hold
- rMotion™ rear suspension
- 15 x 137 x 1.25 in. RipSaw® track
- HPG™ Plus aluminum front shocks
- Brembo brake with braided stainless-steel brake line
- RER™ electronic reverse (E-TEC® engines) / Mechanical reverse (ACE™ engines)
- Warm glove box with 4 L / 1 US gal of storage
- RF D.E.S.S.™ key

## EXTRA HIGHLIGHTS

- ACE™ engines**
- iTC™ Engine mapping modes (Standard, Sport or ECO®)
  - Reversible throttle lever (thumb or finger activated)
  - Engine oil cooler

Renegade®  
ADRENALINE  
850 E-TEC®  
shown



Renegade®  
ADRENALINE  
900 ACE™  
TURBO shown



ROTAX® ENGINE	850 E-TEC®	600R E-TEC®	900 ACE™ TURBO	900 ACE™
Engine details	Liquid-cooled, eRAVE™	Liquid-cooled, eRAVE™	Liquid-cooled, four-stroke D.O.H.C., dry sump, turbocharged	Liquid-cooled, four-stroke D.O.H.C., dry sump
Cylinders	2	2	3	3
Displacement	849 cc / 51.9 in. <sup>3</sup>	599.4 cc / 36.6 in. <sup>3</sup>	899 cc / 54.9 in. <sup>3</sup>	899 cc / 54.9 in. <sup>3</sup>
Bore	82 mm / 3.2 in.	72.3 mm / 2.85 in.	74 mm / 2.9 in.	74 mm / 2.9 in.
Stroke	80.4 mm / 3.2 in.	73 mm / 2.87 in.	69.7 mm / 2.7 in.	69.7 mm / 2.7 in.
Maximum engine speed	7,900 RPM	8,100 RPM	7,750 RPM	7,250 RPM
Carburation	E-TEC direct injection with additional booster injectors	E-TEC direct injection	EFI	EFI
Recommended fuel type	Premium unleaded	Premium unleaded	Premium unleaded	Regular unleaded
Minimum octane	91	91	91	87
Fuel tank	36 L / 9.5 US gal	36 L / 9.5 US gal	36 L / 9.5 US gal	36 L / 9.5 US gal
Oil tank capacity	3.4 L / 3.6 qt	3.4 L / 3.6 qt	3.3 L / 3.5 qt	3.3 L / 3.5 qt

## POWERTRAIN

Drive clutch type	pDrive™ with clickers	pDrive™	pDrive™	pDrive™ with slider shoes
Driven clutch type	QRS	QRS	QRS	QRS
Engagement	3,600 RPM	3,400 RPM	2,200 RPM	2,200 RPM
Small sprocket number of teeth	25	23	25	24
Large sprocket number of teeth	45	45	45	49
Drive sprocket number of teeth	8	8	8	8
Drive sprocket diameter	183 mm / 7.2 in.	183 mm / 7.2 in.	183 mm / 7.2 in.	183 mm / 7.2 in.
Brake system	Brembo brake with stainless-steel braided brake line	Brembo brake with stainless-steel braided brake line	Brembo brake with stainless-steel braided brake line	Brembo brake with stainless-steel braided brake line

DRY WEIGHT	220 kg / 485 lb	217 kg / 478 lb	239 kg / 526 lb	226kg / 499 lb
------------	-----------------	-----------------	-----------------	----------------

## FEATURES

Frame	REV® Gen4	Riser block height	120 mm / 4.7 in.	Mirrors	Optional
Bodywork	Narrow design (E-TEC® engines) <b>Wide design (ACE™ engines)</b>	Starter	Electric	Windshield	430 mm / 17 in.
Skis	Pilot™ 5.7	Reverse	RER™ (E-TEC® engines) Mechanical (ACE™ engines)	Runner	Square 3/8
Seating	Trail performance (E-TEC® engines) <b>Trail with storage (ACE™ engines)</b>	Heated throttle lever/ grips	Standard	Carbide configuration	102 mm / 4 in. at 90°
Handlebar	U-shaped aluminum with J-hooks	Gauge	Analog with display	Hitch	Optional