# PROFESSIONAL SERIES



## **PRE-DAWN IS NO TIME** FOR AMATEUR HOUR. LEAVE IT TO A PROFESSIONAL.

Designed and built for professionals, but also used by homeowners who don't mess around. The Professional Series takes on the deepest, toughest and most treacherous jobs with ease. A massive 23.5" housing and 16" auger team up with a tireless 420cc engine to swallow up to 102 tons of snow per hour and send it flying up to 60 feet.



AUTO-TURN<sup>™</sup> STEERING Zero-degree turning radius



**ENGINE** Reliable Polar Force Pro Briggs and Stratton® engine



HAND WARMERS Stay warm and comfortable



# 16" auger diameter



Available track system for improved traction on any terrain



Available option for infinite speed control







EZ-LAUNCH<sup>™</sup> EFI ENGINE Available EFI engine starts easier and uses less fuel with consistent



power



**DUAL-BELT DRIVE** 

Delivers maximum torque with minimal strain on the belts.



### SKID SHOES Commercial-grade



Maintain unmatched speed, stability and maneuverability.



#### VISIT ARIENS.COM FOR DETAILS



| DESIGNATION             | PROFESSIONAL 36<br>HYDRO EFI   | PROFESSIONAL 32  | PROFESSIONAL 28<br>HYDRO EFI   | PROFESSIONAL 28  | PRO 28 HYDRO<br>RAPIDTRAK   |
|-------------------------|--|--|--|--|---|
| MODEL #                 | 926070   | 926071   | 926068   | 926065   | 926060  |
| STAGE TYPE              | Two Stage   |
| ENGINE POWER            | 420cc (21 ft/lbs)   |
| ENGINE BRAND            | Ariens AX EZ-Launch<br>EFI E-Gov   | Ariens Polar Force by Briggs & Stratton  | Ariens AX EZ-Launch EFI<br>E-Gov   | Ariens Polar Force by Briggs & Stratton  | Ariens Polar Force<br>by Briggs & Stratton  |
| STARTING SYSTEM         | 120V/Recoil  | 120V/Recoil  | 120V/Recoil  | 120V/Recoil  | 120V/Recoil   |
| CLEARING WIDTH          | 36 in (91.4 cm)  | 32 in (81.3 cm)  | 28 in (71.2 cm)  | 28 in (71.2 cm)  | 28 in (71.2 cm)   |
| HOUSING HEIGHT          | 23.5 in (59.7 cm)   |
| THROWING<br>DISTANCE    | 3 ft - 60 ft<br>(.9-18.2 m)   |
| CHUTE TURNING RADIUS    | 200°   | 200°   | 200°   | 200°   | 200°  |
| CHUTE ROTATION          | Quick Turn  |
| DEFLECTOR CONTROL       | Remote   | Remote   | Remote   | Remote   | Remote  |
| TIRE SIZE               | 16 in x 6.5 in<br>(41 x 17 cm)   | 16 in x 6.5 in<br>(41 x 17 cm)   | 16 in x 4.8 in<br>(41 x 12 cm)   | 5.5"W<br>(14 cm)   | 5.5"W<br>(14 cm)  |
| TIRE TYPE               | Directional<br>Snow Tread  | Directional<br>Snow Tread  | Directional<br>Snow Tread  | Directional<br>Snow Tread Track  | Directional<br>Snow Tread Track   |
| STEERING                | Auto-Turn  | Auto-Turn  | Auto-Turn  | Auto-Turn  | Auto-Turn   |
| DRIVE TYPE              | Hydrostatic  | Disc-O-Matic   | Hydrostatic  | Disc-O-Matic   | Hydrostatic   |
| SPEEDS                  | Variable   | 6 Forward / 2 Reverse  | Variable   | 6 Forward / 2 Reverse  | Variable  |
| GEAR CASE               | Cast Iron   |
| GEAR CASE WARRANTY      | 5yr Cons, 5yr Comm  |
| IMPELLER<br>PROFILE     | Steel 3 Blade   |
| IMPELLER DIAMETER       | 14 in (35.6 cm)   |
| AUGER DIAMETER          | 16 in (40.6 cm)   |
| AUGER TYPE              | Steel Serrated  |
| SKID SHOES              | Comm Skids  |
| SCRAPER BAR             | Steel Adjustable  |
| PRODUCT<br>WARRANTY     | 3yr Cons, 1yr Comm  |
| LENGTH                  | 60.3 in (153.2 cm)  |
| WIDTH                   | 38.2 in (98 cm)  | 34.2 in (86.9 cm)  | 30.2 in (118.4 cm)   | 30.2 in (76.7 cm)  | 30.2 in (76.7 cm)   |
| HEIGHT                  | 46.6 in (118.4 cm)  |
| WEIGHT                  | 353 lb (160.1 kg)  | 333.6 lbs (151.3 kg)   | 352 lb (159.7 kg)  | 339.1 lbs (153.8 kg)   | 336.1 lbs (152.5 kg)  |
| FEATURES AT<br>A GLANCE | Halogen Headlight,<br>Handwarmers,<br>Remote Deflector,<br>Electric Start,<br>Drift Cutters,<br>One Hand Interlock | Halogen Headlight,<br>Handwarmers,<br>Remote Deflector,<br>Electric Start, Drift<br>Cutters, One hand Interlock<br>RapidTrak System |