

2024 - 125 RR Specifications

ENGINE

Туре	Beta Built single cylinder, 2- stroke, kick start, liquid cooled, with BPV power valve system.
Bore	54mm
Stroke	54.5mm
Displacement	124.8cc
Compression Ratio	15.2:1
Exhaust Valve	Beta Progressive Valve (BPV)
Ignition	AC-CDI Kokusan
Spark Plug	NGK BR9ECMVX
Lubrication	Premix
Oil Tank Capacity	N/A
Carburetor	Keihin PWK 36mm
Clutch	Wet multi-disk
Transmission	6 Speed
Final Drive	O-ring chain
MSRP	\$8,599.00

CHASSIS

Frame	Molybdenum steel / Double Cradle w/ quick air filter
	access
Wheelbase	58.1"
Seat Height	36.6"
Ground Clearance	12.8"
Footrest Height	16.1"
Dry Weight	207 lbs (wet weight, no fuel)
Fuel Tank Capacity	2.5 US Gallons
Front Suspension	48 mm Sachs Open Cartridge with compression, rebound & spring preload adjustment
Rear Suspension	Aluminum Body Sachs shock w/adjustable rebound and hi/low speed compression
Front Wheel	<u> </u>
Travel	11.6"
Rear Wheel Travel	11.4"
Front Brake	260 mm floating rotor
Rear Brake	240 mm rotor
Front/Rear Rim	21" (Front) 18" (Rear)
Front/Rear Tire	Maxxis Enduro

^{*}Specifications subject to change without notice. Additional information on all models including manuals, accessories, and parts books are available online at www.betausa.com under the support tab.



