



Rolling Packer Specifications

A LANDOLL® Company

Product Attributes	48x48	48x60	60x60	93x60
Approximate Weight (Empty)	10,880 lbs. (4,935 kg)	12,800 lbs. (2,805 kg)	14,220 lbs. (6,450 kg)	13,680 lbs. (6,205 kg)
Working Width	8 ft. 6 in. (2.6 m)	8 ft. 6 in. (2.6 m)	10 ft. 6 in. (3.2 m)	7 ft. 9 in. (2.4 m)
Transport Width	10 ft. 0 in. (3.0 m)	10 ft. 0 in. (3.0 m)	11 ft. 11 in. (3.6 m)	8 ft. 5 in. (2.6 m)
Transport Clearance	N/A	N/A	N/A	12 in. (305 mm)
Overall Length	13 ft. 10 in. (4.2 m)	14 ft. 10 in. (4.5 m)	14 ft. 10 in. (4.5 m)	18 ft. 8 in. (5.7 m)
Number of Drums	2	2	2	1
Length of Each Drum	48 in. (1.2 m)	48 in. (1.2 m)	60 in. (1.5 m)	93 in. (2.4 m)
Drum Diameter - Without Teeth	48 in. (1.2 m)	60 in. (1.5 m)	60 in. (1.5 m)	60 in. (1.5 m)
Drum Diameter - With Teeth	62 in. (1.6 m)	78 in. (2.0 m)	78 in. (2.0 m)	78 in. (2.0 m)
Tooth Size	7 in. x 2.5 in. (178 x 64 mm)	9 in. x 3 in. (229 x 76 mm)	9 in. x 3 in. (229 x 76 mm)	9 in. x 3 in. (229 x 76 mm)
Number of Teeth on Ground	6	6	7	6
Number of Teeth per Drum	72	90	105	165
Total Number of Teeth	144	180	210	165
Total Drum Capacity	752 gal. (2,846 l)	1,175 gal. (4,448 l)	1,468 gal. (5,557 l)	1,090 gal. (4,126 l)
Weight, Filled with Water	17,046 lbs. (7,732 kg)	22,435 lbs. (10,176 kg)	26,257 lbs. (11,910 kg)	22,618 lbs. (10,259 kg)
Weight, Filled with Wet Sand	22,987 lbs. (10,427 kg)	31,280 lbs. (14,188 kg)	36,440 lbs. (16,529 kg)	30,820 lbs. (13,980 kg)
Pressure per Square Inch, Empty	201	237	225	259
Pressure per Square Inch, Water Filled	315	415	416	418
Bearing Surface	9 in. (229 mm)	9 in. (229 mm)	9 in. (229 mm)	9 in. (229 mm)
Hitch	Pintle 360° Swivel Hitch	Pintle 360° Swivel Hitch	Pintle 360° Swivel Hitch	Pintle 360° Swivel Hitch
Transport Tires	N/A	N/A	N/A	(2) 19.5 x 15
Smooth Drum	N/A	N/A	N/A	Optional
Safety Chain Kit	Standard	Standard	Standard	Standard