


MODELS



LS2



The LS2 is our original 4 foot model available with 2 motor sizes. Best for large to mid size tractors.

LS3



The LS3 is our 3 foot model available with 2 motor sizes. Best for compact to small tractors.

MODEL COMPARISON

HYDRAULIC FLOW RATE: SMALL MOTOR
HYDRAULIC FLOW RATE: STANDARD MOTOR
HYDRAULIC FLOW RATE: LARGE MOTOR
WEIGHT
DIMENSIONS
CUTTING DIAMETER
CUTTING CAPACITY
CUTTING POSITIONS
DECK CONSTRUCTION

BLADES
LOADER COMPATIBILITY

MINIMUM REQUIRED TRACTOR WEIGHT

LS2

N/A
8.5-15 GPM
15-20 GPM
450LBS
42"Lx48"Wx29"H
44"
2-3"
11
1/8" Plate
Reinforced with 1/4"
2, Double Sided
SSQA, JD Pin,
Global (Adapter Required)
3,000lbs

LS3

5-8.5 GPM
8.5-15 GPM
N/A
320LBS
34"Lx34"Wx29"H
32"
2-3"
11
1/8" Plate
Reinforced with 1/4"
2, Double Sided
SSQA, JD Pin,
Global (Adapter Required)
2,000lbs

DETAILS & BENEFITS

LaneShark's are equipped with a 1 year limited warranty.

- ↘ Engineered for lower flow hydraulic systems than those on skid steers.
- ↘ An affordable solution for cutting slopes compared to the units used by many local municipalities.
- ↘ The only residential/small farm unit available for cutting vertically. Ideal for for maintaining roads, trails, plantations, hunting lanes, and more.
- ↘ Easily cuts 2-3" saplings, underbrush, and limbs on slopes around ponds and in tight spots.
- ↘ American made using American parts and labor.

**TRACTOR MUST BE EQUIPPED WITH AUXILIARY HYDRAULICS, RETURN MUST GO TO SUMP.
NOT DESIGNED FOR SKID-STEERS.**