



LISTER CULTIVATOR

The LC25 and LC40 Lister Cultivators are designed to provide precise, reliable performance in building, maintaining, and cultivating bedded ground. Each model combines a 3-point mounted toolbar with versatile parallel linkage row units.

The parallel linkage and depth band coulters allow precise depth gauging on individual rows. The machine can be configured as a lister or turned into a row-crop cultivator with rear sweeps.



LISTER CULTIVATOR MODELS

FEATURES & BENEFITS

Lister Cultivator	Tillage Width	Transport Width	Transport Height	Engine H.P. Required	Weight
LC25 8-row 30"	21' 3"	21' 3"	6' 4½"	170+	5750-7050
LC25 8-row 36"	27' 11"	27' 11"	6' 4½"	170+	6000-7300
LC25 8-row 38"	27' 11"	27' 11"	6' 4½"	170+	6000-7300
LC25 8-row 40"	27' 11"	27' 11"	6' 4½"	170+	6000-7300
LC40 16-row 30"	41'	26'	14' 8"	320+	13,000-15,500
LC40 12-row 36"	41'	26'	14' 8"	250+	11,000-13,000
LC40 12-row 38"	41'	24' 8"	14' 8"	250+	11,000-13,000
LC40 12-row 40"	41'	24' 8"	14' 8"	250+	11,000-13,000

LC40 Stack-Fold Model



LC25 Rigid Model



ROW UNIT CHOICES

Lister Cultivators from Great Plains are offered in multiple row unit configurations.

Choices include short or long lister bodies, or short or long cultivator bodies with sweeps and optional barring-off discs. Depth coulters or depth tires are available on either configuration, and side shields can be added.



See www.greatplainsag.com for complete specifications.

Specifications are subject to change without prior notification.

Images may not depict current or standard production models.

ADDITIONAL STANDARD FEATURES



- Heavier 2¼" pins in upper parallel arm pivot
- Laser-cut depth gauges w/ "positive" lock on each row
- Cat. 3/3N or 4/4N 3-point hitch
- Heavy-duty parking stands
- Center 7" x 7" frame w/ ½" wall
- Wing frames are 3/8" wall tubing
- Wide 3-point center frame attachments
- Wider center yokes for added reliability
- LED safety lighting

FIVE WIDTHS OF CULTIVATOR SWEEPS

The cultivator row unit can be equipped with sweeps in 15", 17", 21", 23", or 25" widths to match your row-crop planting width. Ridging wings bury weeds by throwing soil into crop rows. This is an excellent choice for organic farmers looking for non-chemical weed control.



OPTIONS (see website for complete list of features & options)



BARRING-OFF DISCS

CULTIVATOR SHIELD

WING FRAMES LOCK RIGID

Lock the wing frames on folding models to create a rigid frame that effectively distributes weight across the entire machine.

HEAVIER CENTER FRAME

Center 7" x 7" frame with ½" wall provides more strength than most competitive listers.

SAFETY LIGHTS

LED lights for added safety and long bulb life.

