

GRAIN TIPPER









Standard Features

Smooth Surfaces

Inside, Crysteel Grain Tippers are designed with smooth, snag-free sidewalls and steel floors to prevent bridging of loads.

Outside, the smooth sidewalls improve air flow and are great for graphics.

Below, the understructure contains no crossmembers resulting in smooth self-cleaning surfaces that are strong, but without unnecessary weight.

Crysteel Grain Tippers are built with materials and design features that offer years of performance and value:

- Unitized all-welded construction
- High strength 50,000 psi yield steel
- Tubular longbeams, side rails and top rail
- Swing-out 3-section rear gate with rubber seals and large 12" x 24" grain gate in center door
- Rubber-mounted stop, turn, and clearance lights
- 46" side height
- 96" body width

Optional Features

- 60" side height
- 102" body width
- 7 gauge AR floor, ideal for forklift loading
- Crysteel Stingray hoists
- 14" high Tip Tops can be used two-high on 46" sides

Rear Gate Options

- Mesh rear gate with automatic opener/closer
- 2-piece barn door
- · Combo beet/grain
- Sweet corn gate
- · Hydraulic gate
- Center chute available on all except sweet corn or beet



New! Optional hydraulic tailgate.

GRAIN TIPPER

Standard 3-door rear gate with

center grain chute.

Optional mesh rear gate.

Grain ripper opcomoditions											
Inside Body Length in feet		15	16	17	18	19	20	21	22	24	26
46" Sides	Bushel Capacity 96" Body Width	365	389	412	436	460	484	508	532	580	627
	Bushel Capacity 102" Body Width	388	414	439	464	490	515	541	566	617	668
	Approx Weight in Ibs 96" Body Width	2300	2412	2474	2636	2748	2860	2972	3084	3308	3532
90" Sides	Bushel Capacity 96" Body Width	475	507	538	569	600	631	662	693	756	818
	Bushel Capacity 102" Body Width	506	539	572	606	639	672	705	738	804	871
	Approx Weight in Ibs 96" Body Width	2660	2788	2916	3044	3172	3300	3428	3556	3812	4068
14" Tip Tops	Add'l Bushel Capacity 96" Body Width	112	119	127	134	142	149	157	164	179	194
	Add'l Bushel Capacity 102" Body Width	119	127	135	143	150	158	166	174	190	206

Grain Tipper Specifications

CAUTION: The combined weights of truck, body, hoist and load must not exceed the truck's Gross Vehicle Weight rating. Capacities based on water-level load, 50° dump angle, and includes body weight. Some equipment shown may be optional. Specifications subject to change.



CRYSTEEL MANUFACTURING, INC.

Lake Crystal, MN • 1-800-533-0494 • FAX 507-726-2559 www.crysteel.com • E-mail crysteel@tbei.com





Crysteel's Customer Satisfaction Pledge is designed to be the most comprehensive warranty in the truck equipment industry. This pledge covers new products for a period of five (5) years, and is not restricted by vehicle mileage, and begins when the final customer puts our product into service.

This warranty covers our products for defective material and/or workmanship at a rate of 100% for the first (3) years and at a rate of 50% for years 4 and 5.

For more information on Crysteel's 5 Year Warranty, please visit us at www.crysteel.com.