KARCHER

makes a difference

Fleet Aluminum Brightener

Fleet Aluminum Brightener is an extra-strength, acidbased, aluminum cleaner and brightener designed for non-polished aluminum tanks and trailers, aluminum wheels and for preparing aluminum for painting. Fleet Aluminum Brightener is effective in removing grease, oils, baked-on carbon and diesel smoke. This formula is low foaming.

Benefits

- Cleans and Brightens Aluminum
- Economical Dilution Rates
- Fast Rinsing

Dilution Ratio: 1:5 to 1:20, 5 gallons makes 105 gallons

To Apply: DO NOT use on glass, polished aluminum or anodized aluminum. DO NOT use Fleet Aluminum Brightener through the high pressure pump. Use through a downstream injector only to prevent damage to the pump.

Directions: INDUSTRIAL USE ONLY. Read the Safety Data Sheet thoroughly before using this product. For heavy soils, mix with water at a 1:5 dilution rate. For light soils, mix at 1:20 (pH 2.3 at dilution). Rapidly wet surface with diluted Fleet Aluminum Brightener and allow it to stand for a few minutes. Clean entire surface lightly with a pressure washer or brush, then rinse thoroughly with plenty of clean water.

Product Information					Technical Data
Part No.	Size	Gross weight	Dimensions (L x W x H) inches	Ship UPS	Color: Light straw, clear
9.803-746.0	5 gal	52 lbs	12.5 x 12.5 x 15	No	Scent: Sharp
9.803-747.0	55 gal	560 lbs	23.5 x 23.5 x 35	No	Foam 1-5: 3 = Medium to 2 = Low
5.005 747.0	22 Bui	500 105	23.3 × 23.3 × 33	NO	Reaction in Hard Water 1-5: 4 = Fair
					pH at Full Strength: Less than 1

D

2

1

0

Certifications

Kosher Certified for use year round, not including Passover.

Smog & Ozone in accordance with AQMD Rule 102, this product contains 0% photochemically reactive ingredients to contribute to smog or attack the earth's ozone layer.

 $\ensuremath{\text{VOC}}$. This product contains 0.2% California Consumer Products VOC at 1:5 ratio.

North America:

Safety

Personal Protective Equipment

HMIS Safety Rating: Flammability

HMIS Safety Rating: Reactivity

HMIS Safety Rating: Health

4555 Airport Way, Denver, CO 80239, U.S.A. Phone 888-805-9852 | Fax 303-738-2818 | www.karcher.com/us

OSHA/WHMIS/GHS-Compliant SDS available, listed with Infotrac. For emergency spills call 1-800-535-5053. International 1-352-323-3500.

Canada:

6535 Millcreek Drive, Unit 67, Mississauga, ON L5N 2M2, Canada Phone 905-672-8233 | Fax 905-672-3155 | www.karcher.ca

pH at Use Dilution (1:20 Ratio): 2.3



